

BP36V42-3U - 3U External 36V Rack/Tower Battery Pack for select Tripp Lite UPS Systems

MODEL NUMBER: BP36V42-3U





Description

BP36V42-3U rack/tower external battery pack offers extended battery runtime when used in conjunction with expandable 36V Tripp Lite rackmount and tower UPS systems. Includes heavy gauge cabling with high current DC connector for safe, simple installation. Included daisychain connector enables the connection of additional compatible 36V external battery packs to the host UPS. Included mounting accessories support 3U rackmount installation in 4 post racks. Options for 2 post center-mounting and upright tower installation available.

Highlights

- Extends the runtime of expandable 36V DC Tripp Lite UPS Systems
- Included daisychain connector supports the addition of multiple compatible external battery packs
- Supports 3U rackmount installation; 4 post installation accessories included
- Options for 2 post rackmount and tower installation available

Applications

 Ideal means of lengthening the battery runtime provided by compatible Tripp Lite UPS systems

Package Includes

- BP36V42-3U external battery pack with attached DC cabling
- 4 post compatible mounting hardware
- Owner's manual

Compatible with these UPS Systems - SMART1000RMXL2U, SMART1200XLHG, SMART1500RMXL2UA, SMART1500RMXLN, SMART1500XL, SMX1200XLHG, SMX1500XLRT2U and other Tripp Lite UPS systems that specify the use of this battery pack.

Features

- Offers extended-run UPS operation when used in conjunction with compatible 36V DC Tripp Lite UPS systems
- Includes heavy gauge cabling with high current DC connectors for simple installation
- Daisychain connector enables the connection of additional compatible 36V external battery packs to the host UPS
- Included mounting brackets support rackmount installation in 4 post racks using only 3 rack spaces (3U)
- 2POSTRMKITHD option supports balanced 2 point center-mounting in 2 post equipment racks
- 2-9USTAND option enables upright tower placement

Specifications

BATTERY	
Expandable battery runtime	Includes a second input/output connector to daisy-chain multiple battery packs
DC system voltage (VDC)	36
Connects to UPS via	Detachable cable with UPS specific DC connector (36 in length, 6 gauge)



Typical battery lifespan	4-6 years typical (North America)		
PHYSICAL			
Installation form factors supported with included accessories	4 post 19 inch rackmount		
Installation form factors supported with optional accessories	2 post rackmount (2POSTRMKITHD); Tower (2-9USTAND)		
Shipping Dimensions (HWD/in)	11.5 x 23 x 33		
Shipping Dimensions (HWD/cm)	29.2 x 58.4 x 83.8		
Shipping weight (lbs)	190.9		
Shipping weight (kg)	86.7		
Unit Dimensions (HWD/in)	5.25 x 17.5 x 25		
Unit Dimensions (HWD/cm)	13.3 x 44.45 x 63.5		
Unit weight (lbs)	174.1		
Unit weight (kg)	79.0		
Material of construction	Steel		
Form factors supported	3U Rack/Tower		
WARRANTY			
Product Warranty Period (U.S. & Canada)	2-year limited warranty		
Product Warranty Period (International)	1-year limited warranty		
Product Warranty Period (Mexico)	1-year limited warranty		
Product Warranty Period (Puerto Rico)	1-year limited warranty		
Optional Coverage	3 and 5 year warranty extensions available		

Related Items

Optional Products

Model Number	Description	Qty.
WEXT3-BP36V	3-Year Extended Warranty - For All 36V Battery Packs	1
WEXT5-BP36V	5-Year Extended Warranty - For All 36V Battery Packs	1
2-9USTAND	Enables Tower Placement of Rackmount UPS Systems	1
2POSTRMKITHD	Enables 2-Post Rackmount Installation of 3U and Larger UPS, Transformer and Battery Pack Components	1



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

More information, including related products, owner's manuals, and additional technical specifications, can be found online at: http://www.tripplite.com/sku/BP36V42-3U.

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.