

ProtectIt! Surge Suppressor

State of the art protection for every application



Model#: TLP606

- ▶ 6 outlet/6 -ft. cord
- ▶ 750 joule rating
- ▶ \$20,000 Ultimate Lifetime Insurance (USA & Canada only)

Tech Data

Order Now!

Tech Data Part Number:
030254

DESCRIPTION

Tripp Lite's TLP606 offers economical AC surge suppression for protection of workstations, desktop PCs, telecom systems and other sensitive electronics. Built-in AC surge suppression shields connected equipment from damage and performance problems due to transient surges. TLP606 offers 6 total outlets, 6 foot cord and diagnostic LED to warn of suppressor damage. AC suppression rated at 750 joules shields equipment from surges and line noise. Attractive white suppressor housing with keyhole mounting tabs offer convenient protection of desktop computer equipment and accessories. \$20,000 Ultimate Lifetime Insurance (USA & Canada Only).

PLUG/OUTLETS: Input: NEMA5 -15P / Output: 6 NEMA5 -15R / 6 -ft. AC line cord

ELECTRICAL: 120VAC, 50/60Hz, 15A (Requires NEMA5 -15R wall receptacle)

FORMAT: Corded multi -outlet strip with 1 transformer spaced outlet

SUPPRESSION: AC: 150V RMS Clamping / 750 joules / 330V UL1449

KEY BUYING POINTS

- 6 outlets
- 6-ft. cord
- Surge suppression rating: 750 joules
- EMI/RFI noise filtering
- 15 amp resettable circuit breaker
- Green protection LED
- Includes full normal mode (H -N) and common mode (N -G/H -G) line surge suppression
- Can accommodate 1 large transformer plug without covering remaining outlets, 3 total transformers
- Keyhole support for wall mounting
- Lighted power switch
- \$20,000 Ultimate Lifetime Insurance (USA & Canada only)
- Lifetime product warranty

TYPICAL APPLICATIONS

- Ideal for any desktop, network or home computing application requiring AC line protection

PACKAGE INCLUDES

- TLP606surgesuppressor
- Instructionmanualwithwarrantyinformation

COMPLETE SPECIFICATIONS

SYSTEM OVERVIEW	
System overview:	TLP606surgesuppressionstripincludes6ACoutlets,6footACcord,750jouleprotection level,diagnosticLED,lifetimewarrantyand\$20,000connectedequipmentinsurance
Voltage compatibility:	120VAC
Frequency compatibility:	50/60Hz
OUTPUT	
Outputvoltagecapacity(amps):	15
Outputwattcapacity(watts):	1800
Outletquantity/type:	6NEMA5 -15Routputreceptacles
Outletorientation:	Singlerowof6outlets
Transformeraccomodation:	Supports1largetransformerplugaccessorywithoutcoveringremainingoutlets,acceptsup to3transformerstotal
Overloadprotection:	15Aresettableilluminatedcomboswitch/circuitbreaker
INPUT	
Inputconnectiontype:	NEMA5 -15P
Inputcordlength(ft.):	6
Inputcordlength(m):	1.8
Inputcordgauge,type:	14gauge,SJT
Recommendedelectricalservice:	120V15A
LEDS ALARMS & SWITCHES	
DiagnosticLEDs:	Built-inLEDconfirmssuppressor"protectionpresent"(green)status
Switches:	CombinationACcircuitbreakerand2positionredilluminatedon/offpowerswitch
AC SURGE/NOISE SUPPRESSION	
Protectionmodes:	Includesfullnormalmode(H -N)andcommonmode(N -G/H -G)linesurgesuppression
ACsuppressionjoulerating:	750joules
Clampingvoltage(RMS):	150V
ACsuppressionresponsetime:	<1ns
UL1499letthroughrating:	330V -ULVerified
PHYSICAL	
Shippingweight(lbs):	1
Shippingweight(kg):	0.5
Unitweight(lbs):	0.8
Unitweight(kg):	0.4
UnitDimensions(HWD/in):	10.5x1.5x1.5
UnitDimensions(HWD/cm):	26.7x3.8x3.8
ShippingDimensions(HWD/in):	13x4.75x1.9

ShippingDimensions(HWD/cm):	33x12.1x4.8
Materialofconstruction:	Plastic
Integratedkeyholemountingtabs:	Keyholemountingtabsenablewallmounting
Housingcolor:	Attractivegraycolorscheme
AClinecordcolor:	Gray
CERTIFICATIONS	
UL14491998Rev.(ACSuppression):	UL1449
UL1363(PowerTap):	UL1363
cUL/CSA(Canada):	cUL
Approvals:	ExceedsIEEE587categoryA&Bspecifications
WARRANTY	
Productwarranty:	Lifetime
Connectedequipmentinsurance(USAand CanadaOnly):	Upto\$20,000

*The policy of Tripp Lite is one of continuous improvement.
Specifications are subject to change without notice.*