ProtectIt!SurgeSuppressor

Stateoftheartprotectionforeveryapplication





Model#:TLP1008TELTV

- 10outlets/8 -ft.cord
- 1in/2outtel/modemsurgeprotection 1in/1outcoaxialsurgeprotection
- 3345joulerating
- \$150,000UltimateLifetimeInsurance(USA&Canadaonly)withDataRecoveryWarranty

DESCRIPTION

TrippLite'sTLP1008TELTVofferseconomicalACsurgesuppressionforprotectionofworkstations, PCs, telecomsystems, homeelectronics and other sensitive equipment. The TLP1008TLTV features 10 outlets, an 8 -ft. cord with a space -saving right -angle plug, and diagnostic LEDs towarn of suppressor damage. The unith as a surge suppression rating of 3345 joules to shield equipment from line noise and the strongest surges. Built -in RJ11 jacks prevent surges from damaging your modem/fax/phone equipment. Built -in coax jacks prevent surges from damaging your cable/satellite equipment. \$150,000 Ultimate Life time Insurance (USA&Canada Only) with Data Recovery Warranty.

PLUG/OUTLETS:Input:NEMA5 -15P/Output:10NEMA5 -15R/8 -ft.AClinecord

ELECTRICAL:120VAC,50/60Hz,15A(RequiresNEMA5 -15Rwallreceptacle)

FORMAT:Cordedmulti -outletstripwith5transformerspacedoutlet

SUPPRESSION:AC:150VRMSClamping/3345joules/330VUL1449

KEYBUYINGPOINTS

- 10outletswithchildsafetycovers
- 8-ft.cordwithspace -savingright -angleplug
- Built-inRJ11jackspreventsurgesfromdamagingyourmodem/fax/phoneequipment built-insplitterprotectstwodevicessharinga singleline;6 -ft.telephonecordincluded
- Surgesuppressionrating:3345jouleprotection
- EMI/RFInoisefiltering
- 15ampresettablecircuitbreaker
- DiagnosticLEDsconfirmsuppressor"protectionpresent"(green)and"grounded"(red)status
- Includesfullnormalmode(H -N)andcommonmode(N -G/H -G)linesurgesuppression
- Canaccommodateupto5transformerswithoutblockingremainingoutlets
- Built-incoaxjackspreventsurgesfromdamagingyourcable/satelliteequipment;6
 -ft.coaxcableincluded
- Keyholesupportsforwallmounting
- \$150,000UltimateLifetimeInsurance(USA&CanadaOnly)coversconnectedequipmentandincludesDataRecoveryWarranty
- Failsafeshutdownmode
- Lightedpowerswitch
- Lifetimeproductwarranty

TYPICALAPPLICATIONS

 $\bullet \quad \text{Ideal for protecting TVs, DVDs, satellites, stereos and other entertainment systems} \\$

PACKAGEINCLUDES

- TLP1008TELTVsurgesuppressor
- 6-ft.RJ11cable
- 1setnickel -platedcoaxconnectors
- Instructionmanualandwarrantyinformation

COMPLETESPECIFICATIONS

Systemoverview:	TLP1008TELTVsurgesuppressionstripincludes10ACoutlets,8footACcord,singleline
, , , , , , , , , , , , , , , , , , , ,	phonesuppression,coaxlinesurgesuppression,3345jouleprotectionlevel,diagnostic
	LEDs,lifetimewarrantyand\$150,000connectedequipmentinsurance
Voltagecompatibility:	120VAC
Frequencycompatibility:	50/60Hz
OUTPUT	
Outputvoltampcapacity(amps):	15
Outputwattcapacity(watts):	1800
Outletquantity/type:	10NEMA5 -15Routputreceptacles
Outletorientation:	Tworowsofoutlets,including5widelyspacedfortransformers
Outletsafetycovers:	Includesbuilt -inslidingoutletsafetycovers
Transformeraccomodation:	Supports5largetransformerplugaccessorieswithoutcoveringremainingoutlets,acceptsup to8transformerstotal
Overloadprotection:	15Aresettablecircuitbreaker
INPUT	
Inputconnectiontype:	NEMA5 -15P
Inputcordlength(ft.):	8
Inputcordlength(m):	2.4
Inputplugfeatures:	Space-savingrightangleinputplug
Inputcordgauge,type:	14gauge,SJT
Recommendedelectricalservice:	120V15A
LEDSALARMS&SWITCHES	
DiagnosticLEDs:	Built-inLEDsconfirmsuppressor"protectionpresent"(green)and"grounded"(red)status
Switches:	Twopositionon/offpowerswitch
ACSURGE/NOISESUPPRESSION	
Protectionmodes:	Includesfullnormalmode(H -N)andcommonmode(N -G/H -G)linesurgesuppression
ACsuppressionjoulerating:	3345joules
Clampingvoltage(RMS):	150V
ACsuppressionresponsetime:	<1ns
UL1499letthroughrating:	330V -ULVerified
EMI/RFIfiltering:	Upto40dB

TEL/Modemlineprotection:	Includessinglelinephonesuppressionviabuilt -inRJ11connectors,includescable(260V clamping,120joules,center2wiresprotected.1inputjackand2outputjacks)	
Coaxlineprotection:	IncludessinglelinecoaxsuppressionforcableTV,cablemodemandotherdevices supportingtypeFcoaxconnections	
PHYSICAL		
Unitweight(lbs):	2.2	
Unitweight(kg):	1.0	
UnitDimensions(HWD/in):	11.6x5x2.25	
UnitDimensions(HWD/cm):	29.5x12.7x6.5	
ShippingDimensions(HWD/in):	14.75x7.75x2.3	
ShippingDimensions(HWD/cm):	37.5x19.7x5.8	
Materialofconstruction:	Plastic	
Integratedkeyholemountingtabs:	Keyholemountingtabsenablewallmounting	
Housingcolor:	Metallicsilver	
AClinecordcolor:	Black	
CERTIFICATIONS		
UL14491998Rev.(ACSuppression):	UL1449	
UL1363(PowerTap):	UL1363	
UL497A(Communications):	UL497A	
FCCPart68(Communications):	FCCPart68	
cUL/CSA(Canada):	cUL	
IndustryCanada(Communications):	IndustryCanada	
Approvals:	ExceedsIEEE587categoryA&Bspecifications	
WARRANTY		
Productwarranty:	Lifetime	
Connectedequipmentinsurance(USAand CanadaOnly):	Upto\$150,000	
Datarecoverywarranty:	Included	

The policy of Tripp Lite is one of continuous improvement. Specifications are subject to change without notice.