



### Features

- Mini-ITX system supports IBASE Mini-ITX motherboards
- Available in black color
- Supports 2x PCI slots
- With motherboard's I/O shields and extra 2x USB ports
- LEDs for Standby and Power
- One 3.5" HDD drive bay
- Optional 250W DC power supply
- Supports desktop or wall mount mounting

### CMI203 Specifications

System Mainboard	IBASE Mini-ITX motherboards
Construction	SECC
Chassis Color	Black
Multi-function interface board	ID723
I/O Connectors	Flexible IBASE Mini-ITX motherboard's I/O shields, extra 2x USB ports, Standby LED, Power LED, ATX power On/Off/Reset, 2x 12V DC output connectors
Expansion Slots	2x PCI slots
Storage	1x 3.5" HDD drive bay
Mounting	Desktop or wall mount
Dimensions	340(W) x 100(H) x 225(D)mm (13.39" x 3.94" x 8.89" )
Power Supply	Output Power:AC 180W & 250W (ATX) Input Voltage:90~264VAC full range

### Environmental/Mechanical

Operating Temperature	0°C~ 45°C (32°F~113°F)
Relative Humidity	90% @ 40°C, (non-condensing)
RoHS Compliance	Available

### Ordering Information

CMI203-180	Chassis for Mini-ITX, w/ 180W PSU, 3.5" HDD holder, mounting brackets, 2x PCI-E (optional IP241, IP118-R riser card & iLO LCM)
CMI203-250	Chassis for Mini-ITX, w/ 250W PSU, 3.5" HDD holder, mounting brackets, 2x PCI-E (optional IP241, IP118-R riser card & iLO LCM)
MI935	LGA775 Intel® Core™2 Duo Mini-ITX motherboard w/ Intel® Q35 chipset (see page 64)
MI932	Socket AM2 AMD Athlon 64 Mini-ITX motherboard w/ AMD M690E chipset (see page 74)
MI930	AMD Athlon™ 64 / Socket AM2 Mini-ITX motherboard w/ AMD M690T chipset (see page 75)
MI910	Socket 478 Intel® Core™2 Duo Mini-ITX motherboard w/ Intel® GME965 chipset (see page 65)
MI900	LGA775 Intel® Core™2 Duo Mini-ITX motherboard w/ Intel® Q965 chipset (see page 66)
MB899	Socket 478 Intel® Core™2 Duo Mini-ITX motherboard w/ Intel® 945GME chipset (see page 68)
MB899X	Socket 478 Intel® Core™2 Duo Mini-ITX motherboard w/ Intel® 945GME chipset (see page 67)
MB896	Socket 479 Pentium® M/Celeron® M Mini-ITX motherboard w/ Intel® 915GME chipset (see page 70)
MB850	Socket 478 Pentium® 4(M) Mini-ITX motherboard w/ Intel® 845GV chipset (see page 72)
MB770	VIA Eden-V4/C7 Mini-ITX motherboard w/ VIA CN700 chipset (see page 73)
MB740	AMD Geode NX Mini-ITX motherboard/chipset (see page 76)
IP118	Riser card with 1x PCI-E(x16) (see page 34)
IP241-R	Riser card with 2x PCI (see page 34)

Remarks: 1. Use only CPU/heatsink with height fitting the chassis-not touching the chassis top cover.  
2. ODM/OEM is available.