

VGA Desktop LCD MONITOR

Model: FPT-170AA
beige color

Model: FPT-170AB
black color



Features

- * "Designed for touch" stable photo stand
- * Standard VGA(DB-15) analog Plug-and-Play
- * Superior viewing angles, contrast ratio, and brightness
- * Built-in two 1.5W speakers with amplifier
- * User friendly OSD controls
- * Worldwide agency approvals

Options

- * Durable touchscreen
- * CM-330 VGA-to-Video adapter
- * AMS-0011 Media Station

Touchscreen Monitor Models

- FPT-170AATEAR**
Beige 5-Wire Resistive RS232 Touch Monitor
- FPT-170ABTEAR**
Black 5-Wire Resistive RS232 Touch Monitor
- FPT-170AATEARU**
Beige 5-Wire Resistive USB Touch Monitor
- FPT-170ABTEARU**
Black 5-Wire Resistive USB Touch Monitor
- FPT-170ABTEAS**
Black Acoustic Wave RS232 Touch Monitor
- FPT-170ABTEASU**
Black Acoustic Wave USB Touch Monitor
- FPT-170AATMAC**
Beige Capacitive RS232 Touch Monitor
- FPT-170ABTMAC**
Black Capacitive RS232 Touch Monitor
- FPT-170AATMACU**
Beige Capacitive USB Touch Monitor
- FPT-170ABTMACU**
Black Capacitive USB Touch Monitor

Specifications

LCD Panel

TFT Active Matrix color
17 in (432 mm) diagonal viewable
SXGA 1280 x 1024 resolution (maximum)
0.264 x 0.264 mm pixel pitch
16 million displayable colors
250 nit brightness (typical)
80% brightness uniformity (minimum)
400:1 contrast ratio (typical)
25 ms response time (typical at 25°C)
170° (H), 170° (V) viewing angle (minimum)
50,000 hours MTBF (minimum at 25°C)

Video Interface

RGB analog D-sub 15 pin
24-62 kHz horizontal scan
50-75 Hz vertical refresh

On-Screen Display (OSD)

Brightness, Contrast, Phase, Clock, Volume, H&V
Position, Auto-tune, Recall

Regulatory

Safety: UL/CUL, TUV-GS, CB
EMI: FCC(DOC), VCCI, CE
Ergonomics: TCO99 (optional)

Power Management

meet VESA DPMS & Energy Star requirements
5W sleep mode, 30W normal mode
IEC 320/EN 60320 Power Inlet

Mechanical and Environment

Operation temperature: 0~50°C [32~122°F]
Storage temperature: -20~65°C [-4~149°F]
Humidity: 10~85% (operating), 10~90% (storage)
Altitude: 0~10,000 ft (operating), 0~40,000 ft (storage)
393.7 x 330.2 x 69.85 mm [15.5 x 13 x 2.75 inch]
15 lbs/ 6.8 kg

Others

75 x 75 mm VESA mounting holes
1.5W speaker x 2 with amplifier

Photo Frame Rear View

