

Media Signage LCD DISPLAY

Model: MD-15
color: black



Features

- * CF card stopper to prevent memory card theft
- * Firmware-lockable power on/off and other switches (On Screen Display) to prevent public unauthorized access
- * Convenient lid for future firmware updating/upgrading
- * Semi-hidden power on/off and other adjustment (On Screen Display) switches
- * Automatic repeat playback for looped video advertising
- * Built-in rotary counter for switching between presentation groups
- * Displays JPEG/motion, JPEG, MP3, MPEG1, MPEG2, MPEG4(AVI), and VOB formats for retail TV and video advertising
- * IR remote controlled sound level
- * 100 x 100 mm VESA standard digital signboard mounting holes easily match third party mounting kits
- * Integrated audio speakers

Specifications

LCD Panel	Mechanical and Environment
TFT Active Matrix color	Operation temperature: 0~50°C [32~122°F]
15 in/381 mm diagonal viewable	Storage temperature: -20~60°C [-4~140°F]
250 nit brightness (typical)	Humidity: 85% (maximum)
80% brightness uniformity (minimum)	369 x 275 x 43 mm [14.53 x 10.83 x 1.69 inch]
500:1 contrast ratio (typical)	5.5 Kg/ 12.1 lbs
12 ms response time (typical at 25°C)	
150° (H), 150° (V) viewing angle (minimum)	
30,000 hours MTBF (minimum at 25°C)	
Package Includes	Input and Output
15" MPEG LCD display	Compact Flash Slot
AC Power Cord	USB 2.0
	Power Management
	VESA DPMS standard
	12V Universal Input Adapter

Options

- * Motion Sensor
- * Front anti-reflective protection glass

