

# Power Supply

PS/2 AC Input AT Type



## ACE-940AP

**390W**



**PFC**



Input Type	95 ~ 264VAC Full Range					
Output Voltage	+3.3V	+5V	+12V	-5V	-12V	+5Vsb
		40A (2A min)	15A (0.2A min)	0.3A	0.8A	
Efficiency	65%					
Temperature	0 ~ 50°C (Operating), -20 ~ 80°C(Storage)					
MTBF(hrs)	100,000					
Output Connector	P8+P9 x1, Extra +5V(P10) x1, HDD/CDROM x8, FDD x2					

### Ordering Information

- **ACE-940AP-RS**  
390W AC-DC PS/2 AT Power Supply, with PFC

## ACE-932A

**300W**



Input Type	85 ~ 130VAC, 180 ~ 265VAC Auto Range					
Output Voltage	+3.3V	+5V	+12V	-5V	-12V	+5Vsb
		33A (3A min)	8A (0.2A min)	0.5A	3A	
Efficiency	68%					
Temperature	Operating : 0 ~ 50°C (50 ~ 70°C derating curve) Storage : -40 ~ 75°C					
MTBF(hrs)	120,000					
Output Connector	P8+P9 x1, Extra +5V(P10) x1, HDD/CDROM x4, FDD x2					

### Ordering Information

- **ACE-932A-S-RS**  
300W AC-DC PS/2 AT Power Supply

## ACE-925M

**Medical**

**200W**



Input Type	90 ~ 264VAC Full Range					
Output Voltage	+3.3V	+5V	+12V	-5V	-12V	+5Vsb
		22A (4A min)	7A (1A min)	0.5A	0.5A	
Efficiency	65%					
Temperature	Operating : 0 ~ 70°C (40 ~ 70°C derating curve) Storage : -40 ~ 75°C					
MTBF(hrs)	110,000					
Output Connector	P8+P9 x1, HDD/CDROM x5, FDD x2					

### Ordering Information

- **ACE-925M-RS**  
200W AC-DC PS/2 AT Power Supply, meet Medical standard

## ACE-935AL

**300W**



Input Type	85 ~ 140VAC, 170 ~ 270VAC Auto Range					
Output Voltage	+3.3V	+5V	+12V	-5V	-12V	+5Vsb
		40A (3A min)	8A (0.1A min)	0.3A	0.7A	
Efficiency	68%					
Temperature	0 ~ 50°C (Operating), -40 ~ 75°C(Storage)					
MTBF(hrs)	100,000					
Output Connector	P8+P9 x1, Extra +5V(P10) x1, HDD/CDROM x5, FDD x2					

### Ordering Information

- **ACE-935AL-RS**  
300W AC-DC PS/2 AT Power Supply, AC select switch

## ACE-925A/AP

**200W**



**PFC**



Input Type	85 ~ 265VAC Full Range					
Output Voltage	+3.3V	+5V	+12V	-5V	-12V	+5Vsb
		22A (1A min)	7A (0.1A min)	0.5A	0.7A	
Efficiency	68%					
Temperature	0 ~ 50°C (Operating), -40 ~ 75°C(Storage)					
MTBF(hrs)	130,000 (ACE-925A), 140,000 (ACE-925AP)					
Output Connector	P8+P9 x1, HDD/CDROM x5, FDD x2					

### Ordering Information

- **ACE-925A-RS**  
200W AC-DC PS/2 AT Power Supply
- **ACE-925AP-RS**  
200W AC-DC PS/2 AT Power Supply, with PFC

## ACE-920A

**150W**



Input Type	85 ~ 265VAC Full Range					
Output Voltage	+3.3V	+5V	+12V	-5V	-12V	+5Vsb
		20A (1A min)	4A (0.1A min)	0.5A	0.5A	
Efficiency	68%					
Temperature	0 ~ 50°C (Operating), -40 ~ 75°C(Storage)					
MTBF(hrs)	160,000					
Output Connector	P8+P9 x1, HDD/CDROM x3, FDD x2					

### Ordering Information

- **ACE-920A-RS**  
150W AC-DC PS/2 AT Power Supply