

# CPU Cooler

High performance thermal solutions



The faster CPU runs and higher voltage it supplies, the more heat it gets and higher noise it emits. To avoid the computer system shut down, which is decided by whether you have chosen a suitable CPU cooler. For Industrial application., IEI provides a series of CPU Cooler to fit in with different kind of thermal resistance.

## Pentium® 4 (LGA-775)

130W

**CF-775A-RS**  
High Performance Two Copper Pipes LGA 775 CPU Cooler, RoHS



	CF-775A-RS
Dimensions (DxWxHmm)	92x92x73
Material	Cu-Al
Bearing Type	Rifle
Capability (Watt)	130W
Fan speed (RPM)	3600
Noise level (dBA)	36.6~39.6
Life expectancy (hrs)	40000
G.W. (g)	492

## Pentium® 4-M (LGA-775)

90W

**CF-775B-RS**  
High Performance 1U LGA 775 CPU Cooler , w/ 7010 fan, Cooper , RoHS



	CF-775B-RS
Dimensions (DxWxHmm)	90x90x25.1
Material	Cu
Bearing Type	Two ball
Fan speed (RPM)	4800
Noise level (dBA)	40.3~44.3
Life expectancy (hrs)	50000
G.W. (g)	600

## Pentium® 4 (LGA-775)

115W

**CF-520-RS**  
High Performance LGA 775 socket CPU Cooler , RoHS



	CF-520-RS
Dimensions (DxWxHmm)	115x115x67
Material	Aluminum Alloy
Bearing Type	Two ball
Capability (Watt)	115W
Fan speed (RPM)	4500
Noise level (dBA)	47.5~51.5
Life expectancy (hrs)	70000
G.W. (g)	635

## Pentium® 4 (Socket-478)

115W

**CF-478A-RS**  
High Performance Copper Socket 478 CPU Cooler , RoHS



	CF-478A-RS
Dimensions (DxWxHmm)	92x92x67
Material	Cu
Bearing Type	Rifle
Capability (Watt)	115W
Fan speed (RPM)	3600
Noise level (dBA)	39.6
Life expectancy (hrs)	40000
G.W. (g)	390

## Pentium® 4 (Socket 478)

86W

**CF-478B-RS**  
High Performance Heat pipe Socket 478 1U CPU Cooler, RoHS



	CF-478BA-RS
Dimensions (DxWxHmm)	89x76x26
Material	Cu-Al
Bearing Type	Two ball
Capability (Watt)	86W
Fan speed (RPM)	4800
Noise level (dBA)	37
Life expectancy (hrs)	40000
G.W. (g)	204

## Pentium® 4 (Socket 478)

86W

**CF-514-RS**  
High Performance Skiving Pentium 4 CPU Cooler, RoHS



	CF-514-RS
Dimensions (DxWxHmm)	83x70x55
Material	Aluminum Alloy
Bearing Type	Two ball
Capability (Watt)	86W
Fan speed (RPM)	4800
Noise level (dBA)	42.4
Life expectancy (hrs)	50000
G.W. (g)	284

## Pentium® 4

86W

**CF-521-RS**  
High Performance Socket-478 Pentium 4 CPU Cooler(60x60) , RoHS



	CF-521-RS
Dimensions (DxWxHmm)	60x60x47
Material	Al
Bearing Type	Two ball
Capability (Watt)	86W
Fan speed (RPM)	4800
Noise level (dBA)	37
Life expectancy (hrs)	40000
G.W. (g)	173

## Pentium® 4

76W

**CF-522-RS**  
High Performance Socket-478 1U Pentium 4t CPU Cooler , RoHS



	CF-522-RS
Dimensions (DxWxHmm)	60x60x30
Material	Al
Bearing Type	Two ball
Capability (Watt)	76W
Fan speed (RPM)	4800
Noise level (dBA)	37
Life expectancy (hrs)	50000
G.W. (g)	120