



System

CPU	Intel® Core™2 Quad / Core™2 Duo / Celeron® 400 Sequence processors (Conroe-L)
System Memory	4x DDR2 667/800 DIMM, Max. 8GB
System Chipset	Intel® Q35 Express + ICH9, 800/1066/1333MHz FSB
BIOS	Award
Watchdog Timer	256 levels
SSD	CF Socket
H/W Monitor	Yes
Expansion Slot	1x PCI32 interface for backplane use

Graphics

VGA Controller	Intel® Q35 Express integrated
VGA Memory	DVMT 4.0 (Intel® GMA 3100); supports memory allocation up to 256MB
LCD Interface	N/A

LAN

Controller	6x Intel® 82573L Gigabit LAN with Bypass on LAN1/2
Connector	RJ-45 on board

Multi I/O

I/O Chipset	Winbond W83627EHG + Fintek F81216 1x IDE1 (PCI to PATA), 1x CF socket (IDE2), 1x KB, 1x Mouse, 4x RS-232, 4x SATA II
USB	2 ports on board Pin header for 2 ports (USB 2.0)
Audio	N/A

Features

- Supports Intel® Core™2 Quad / Core™2 Duo / Celeron® 400 Sequence processors (Conroe-L), 800/1066/1333MHz FSB
- 4x DDR2 DIMM, Max. 8GB
- 6x Intel® Gigabit LAN, LAN1/LAN2 Bypass
- Integrated VGA, CRT support
- 4x SATA II, 4x COM, 4x USB 2.0, 1x IDE
- 1x CF socket, 1x PCI32 interface for backplane

Mechanical and Environmental

Dimensions	355mm x 185mm (14" x 7.3")
Max. Power Requirement	TBC
Operating Temperature	0°C~60°C (32°F~140°F)
Storage Temperature	-20°C~80°C (-4°F~176°F)
Relative Humidity	10%~90% (non-condensing)

Ordering Information

MB935	LGA775 Q35 Networking motherboard with 6x GbE LAN, LAN1/2 Bypass, VGA, 4x SATA II
IP325	Riser card for MB935 w/ 2x PCI slots

Remarks:
* Specifications are subject to change without prior notice.