WebDT 515/517

Display-Integrated Digital Terminal for Vertical Computing



DT Research designs and manufactures a comprehensive line of network-ready information appliances, enabling secure and reliable access to the Internet and applications anytime, anywhere. The WebDT 515 and 517 LCD-integrated thin clients provide efficient computing in a sleek, small footprint design. Whether wireless, on a desktop, or mounted, these devices efficiently adapt to many applications.



Key Features:

- Elegant all-in-one, slim, space saving design
- Fan-less, high performance operation
- High contrast LCD panel with wide viewing angle
- Low power consumption
- IR touch screen option
- VESA-mountable for flexibility in mounting and deployment
- Optional integrated 802.11 a/b/g wireless LAN adapter
- Comprehensive software for remote monitoring, control, and upgrade
- Optional magnetic card reader

The WebDT 515 and 517 digital terminals integrate vivid displays with efficient computing in one slim, mountable design. The WebDT 515 and 517 feature the integration of bright 15" and 17" LCD displays, respectively, over an efficient and powerful x86 1.5GHz-powered thin client platform, with optional IR touch screen, internal wireless communication, magnetic stripe reader. The full-featured yet elegant, space-saving package accommodates a range of accessories and peripherals to support a wide variety of vertical applications.

Applications:

The WebDT 515/517 is ideal for the following applications:

Kiosk

Hospitality

• Retail

- · Control and Monitoring
- Entertainment/ Gaming
- Finance
- Education
- Healthcare
- Manufacturing





Specifications:			
Display	WebDT 515: 15" or WebDT 517: 17" TFT LCD		
Display Resolution	WebDT 515: Up to 1024 x 768; WebDT 517: Up to 1280 x 1024		
Processor	1.5 GHz x86 processor		
Memory (RAM)	1GB		
Operating Systems	Windows® XP Embedded or Windows® XP Professional		
Storage	2GB, 4GB, 8GB or 16GB flash module; 2.5" SATA HDD		
Display Enclosure	ABS + PC Plastic		
Base or Pedestal	Detachable aluminum construction; VESA- compliant mounting		
Control Buttons	Five (5) side buttons: • Power (1) • Programmable (4)		
Input/ Output Ports	DC-in jack	USB 2.0 port (4)	Mic-in jack
	Serial Port (1)	Ethernet port (RJ45)	Line-in jack
	Video-in RCA port	Audio out jack	
Stereo Speakers	Built-in speakers		
Network Interface	Ethernet 10/100 MB Base-T LAN; 802.11a/b/g WLAN		
AC/DC Adapter	Input voltage 100~240V AC, 50/60 Hz; Output: 18.5V, 3.5A		
Power Cords	North America, EU, UK, China		
Dimensions With Base Stand (H x W x D)	WebDT 515 356 x 354 x 171 mm; 14 x 13.9 x 6.7 in		
	WebDT 517 409 x 388 x 171 mm; 16.1 x 15.3 x 6.7 in		
Dimensions Without Base Stand (W x H x D)	WebDT 515 278 x 354 x 63 mm; 10.9 x 13.9 x 2.5 in		
	WebDT 517 320 x 388 x 68 mm; 12.6 x 15.3 x 2.7 in		
Weight (With Base Stand)	WebDT 515: 6 kg/13.2 lbs; WebDT 517: 7 kg/ 15.4 lbs		

Major Options:

Regulatory

Humidity

• Built-in 802.11a/b/g WLAN

Weight (Without Base Stand)

Operating Temperature

- IR touch screen
- Magnetic card reader
- * Options subject to change without notice.



WebDT 515: 4.8 kg/10.6 lbs; WebDT 517: 5.8 kg/ 12.8 lbs

FCC Class B, CE, C-Tick, RoHS compliant





0°C - 40°C

0% - 90% non-condensing

^{*} Specifications subject to change without notice.