


# FEATURES & BENEFITS

- DB25 male connectors
- RS-232/422/485 software-selectable ports
- Communications speeds up to 460Kbps
- 25KV surge protection
- Rugged steel encolsure
- Works with RocketPort INFINITY or EXPRESS cards
- RoHS compliant

Part Number 30075-5

# **Product Description**

The next-generation RocketPort 16-Port Surge Interface has sixteen DB25M connections that can be configured for RS-232/422/485 serial communications at speeds up to 460Kbps. The interface is connected to the required RocketPort controller card through a host interface cable.





# SPECIFICATIONS

#### HARDWARE

• Dimensions	8.5″ x 0.9″ x 5.8″
• Product Weight	32 oz
ELECTRICAL SPECIFICATIONS	

#### Device

# ESD Surge Protection 25KV (min)

# ENVIRONMENTAL SPECIFICATIONS

<ul> <li>Air temperature</li> </ul>	
System On	0 to 60° C
System Off	-20 to 85° C
<ul> <li>Operating Humidity</li> </ul>	
Non-condensing	5% to 95%
• Altitude	0 to 10000 Feet
• MTBF	31.4 Years

#### SERIAL COMMUNICATIONS

<ul> <li>Connector Type</li> </ul>	(16) DB25M	
<ul> <li>Supported Standards</li> </ul>		
RS-232		
RS-422		
RS-485 Full Duplex Master/Slave (4-wire)		
RS-485 Half Duplex (2-wire)		
Baud Rate	300 to 460.8Kbps	
Device Driver Data Control		
Modem Control Signals	RTS, CTS, DSR,	
_	DTR, CD, RI	

## EXPORT INFORMATION

## **REGULATORY STANDARDS**

Emission:

- Emissions Canadian EMC Requirements ICES-003 European Standard EN55022
  - FCC Part 15 Subpart B
  - Class A Limit AS/NZS CISPR 22
- Immunity:
  - European Standard EN55024
    - IEC 1000-4-2/EN61000-4-2: ESD
    - IEC 1000-4-3/EN61000-4-3: RF
    - IEC 1000-4-4/EN61000-4-4: FAST TRANSIENT
    - IEC 1000-4-5/EN61000-4-5: SURGE
    - IEC 1000-4-6/EN61000-4-6: CONDUCTED DISTURBANCE
  - DISTURBANCE
  - IEC 1000-4-8/EN61000-4-8: MAGNETIC FIELD IEC 1000-4-11/EN61000-4-11: DIPS AND VOLTAGE VARIATIONS
- Safety
  - IEC 60950/EN60950
  - CSA C22.2 No. 60950/UL60950 Third Edition
- Other
  - European Standard: 2002/95/EC Directive (RoHS)

## REGULATORY APPROVAL MARKS

- RoHS 2002/95/EC • CE
- C-Tick
- UL/cUL

#### FEATURES

• 5 Year Warranty



## APPLICATIONS

- Point of Sale
- Kiosks
- Material Handling
- Hospitality
- Medical
- CNC/DNC
- Remote Access
- Automatic Data Collection
- Industrial Control and Monitoring

#### ORDERING INFORMATION

#### 30075-5 RocketPort 16-Port DB25M Surge Interface

# PRODUCT SUPPORT & SERVICE INFORMATION

Warranty Information Comtrol offers a 30-day satisfaction guarantee and 5-year limited warranty.

Sales Support +1.763.494.4100 sales@comtrol.com

Technical Support +1.763.494.4100 www.comtrol.com/support

Email, FTP and Web Support info@comtrol.com ftp.comtrol.com www.comtrol.com