Digi Passport®

Integrated Console Server

The Digi Passport offers secure, reliable in- and out-ofband management for servers, routers, switches, firewalls and other network devices.



Overview

The Digi Passport provides secure remote access for computer systems and network equipment. It supports serial console connections, service processor connections to the leading server vendors, as well as SMASH extensions to network-based access protocols. Capable of communicating with virtually any server or device, the Digi Passport is ideal for cross-platform equipment support.

Digi's *free*KVMTM allows secure access to a system's BIOS, OS and graphical desktop from a single interface. Users can manage multiple servers without the cost or complexity of most KVM over IP solutions.

Automatic Device Recognition auto-configures attached devices and populates the Title page with device details. It also monitors the ports and sends alerts for disconnected or down devices.

The Digi Passport, used in conjunction with the Digi Remote Power Manager, offers comprehensive infrastructure management. Users can remotely power on/off connected devices, reboot servers, and receive notifications of changes in power usage, temperature readings, system reboots and more.



Administrator Workstation Primary Ethernet Digi Passport Sun Server Windows Server 2003 Features/Benefits Supports all common operating systems including

- Windows Server® 2003
- SSH and SSL/TLS ensure secure connections

Linux®, Mac OS® X, Solaris®, UNIX,

- Port buffering/logging for detailed troubleshooting
- Secure clustering allows multi-server access via one IP address
- Advanced customizable scripting
- Dual Ethernet and optional dual power provide redundant connectivity and power
- IPv4/IPv6 dual stack
- Configurable email/pager alerts and SNMP traps



| | Digi Passport® 4 | Digi Passport® 8 | Digi Passport® 16/32/48 | |
|---|---|--|--|--|
| Features | | | | |
| Authentication | RADIUS, TACACS+, Secure LDAP, Active Directory and Kerberos | | | |
| Security | SSH server/client; SSL; IP filtering; Data capture via port buffering and logging (syslog-ng and NFSv3) | | | |
| Management | Command Line; Web (HTTP/HTTPS); SNMPv3; PPP; RIP; Multi-level menuing; Port triggers, alerts and SNMP traps | | | |
| Operating Systems | Embedded Linux (Linux Kernel 2.6.12 Distribution) | | | |
| Programming Language | Perl scripting for advanced log searching and alerting | | | |
| Connections | Straight-through CAT5 cables for serial and Ethernet connections | | | |
| Port Access | HTTPS/HTTP, SSH/Telnet to a customizable menu; SSH/Telnet directly to the port by name, port specific socket or specified IP number per port; Multiple users per port; Simultaneous SSH sessions on all ports | | | |
| Supported PC Cards | PCMCIA/CF memory cards, Wireless LAN adapter (802.11b), Ethernet LAN adapter, PSTN/CDMA modem card | | | |
| Supported Remote Power Management Controllers | Digi Remote Power Manager, BayTech, Server Technology | | | |
| Supported Service Processor | ALOM, DRAC, iLO, ILOM, IPMI v2.0, Phantom/Roamer, (SMASH extensions supported) | | | |
| Rack Mount | - | 19" rack mou | 19" rack mount kit included | |
| Dimensions (L x W x H) | 8.00 in x 6.20 in x 1.10 in (20.30 cm x 15.50 cm x 2.90 cm) | 17.50 in x 8.00 in x 1.80 in (44.30 cm x 20.30 cm x 4.40 cm) | 17.50 in x 10.00 in x 1.80 in (44.30 cm x 25.30 cm x 4.40 cm) | |
| Weight | 2.06 lb (0.94 kg) | 5.19 lb (2.28 kg) | 16-port: 6.09 lb (2.78 kg); 32-port: 6.23 lb (2.85 kg); 48-port: 6.48 lb (2.96 kg); Dual power models: add 0.20 lb | |
| Interfaces | | | | |
| Serial Ports | 4 RJ-45 RS-232 | 8 RJ-45 RS-232 | 16, 32 or 48 RJ-45 RS-232 | |
| Console Ports | 1 RJ-45 RS-232 | | | |
| Ethernet Ports | 2 RJ-45 10/100Base-T | | | |
| USB Ports | 1 USB 2.0 | | | |
| PC Card Slot | - | One 16-bit PCMCIA | | |
| Power Requirements | | | | |
| Power Supply | External 5V, 4A adaptor | Internal 100-240VAC, 50/60 Hz, 0.37A max, 15W (power output side) | | |
| Power Supply MTBF | 11 years | | | |
| Environmental | | | | |
| Operating Temperature | 0° C to 50° C (41° F to 122° F) | | | |
| Storage Temperature | -30° C to +60° C (-20° F to +140° F) | | | |
| Regulatory Approvals | | | | |
| Safety | UL 1950, EN60950 | | | |
| Emissions/Immunity | CE, FCC Part 15 (Class A), EN55024, EN55022 (Class A) | | | |
| RoHS Compliant | Yes | | | |







Visit www.digi.com for part numbers.

Digi International

DIGI SERVICE AND SUPPORT - You can purchase with confidence knowing that Digi is here to support you with expert technical support and a strong five-year warranty. www.digi.com/support

BUY ONLINE • www.digi.com

Digi International 877-912-3444

France 952-912-3444 +33-1-55-61-98-98 info@digi.com www.digi.fr

Digi International KK

+81-3-5428-0261 www.digi-intl.co.jp **Digi International** (HK) Limited +852-2833-1008

www.digi.cn



91001363 C1/509