

JetNet 3010G

Industrial 7+3G Gigabit Ethernet Switch



- 7 10/100 TX ports and 3 Gigabit RJ-45/SFP combo ports
- 32Gbps Switch Fabric with excellent data exchange performance
- Support 1.2KV Hi-Pot isolation protection
- Redundant power input DC 12~48V
- Auto Gigabit RJ-45/SFP module detection
- IEEE 802.1p for Quality of Service (QoS)
- Aluminum case with IP-31 grade protection
- -20~70°C operating temperature for hazardous environment application



Overview

The Korenix JetNet 3010G is an Unmanaged Industrial Switch, which is equipped 7 ports RJ-45 10/100Mbps and 3 ports Gigabit TX with SFP combo.

The SFP ports are compatible with all types of SFP Transceiver, which could be Gigabit SX, LX, LHX, ZX and XD for several of connections and distances.

Flexibility — 1000Mbps SFP / Combo Ports

The 3 combo ports lead to the flexibilities and the conveniences for additional fiber connections with just plug-in different types of SFP modules, from 2KM multi-mode to 120KM single-mode. The combo ports also make the port-combination easier, such as 8 RJ ports and 2 fiber ports, or 9 RJ ports and 1 fiber port. The standard 10 port Fast Ethernet Switch greatly shortens normal long lead time by the special fiber switch model and reduces the total cost for fiber uplink network.




Quality of Service (QoS)

JetNet 3010G focus on the cost effective application which allocates lot of Fast Ethernet devices and provides higher bandwidth to Gigabit Backbone Switch.

The 32Gbps Switch Fabric and IEEE802.1p Quality of Service (QoS) mechanism enlarge and extend field site network transmission performance.


Brilliant Idea for Hazardous Environment Application Robust Mechanism Design

Korenix JetNet 3010G's outstanding outlook is rock-solid and fashionable with strong functionality. The special fan-less heating dispersing mechanical design adapts the thermodynamic technique to ventilate heat generated from Ethernet module efficiently. Using aluminum extrusion case with industrial quality, IP 31 class of protection, light weight, rigid shell and excellent thermal conductivity units can operate under harsh industrial environment reliably.



- Industrial PoE Switch
- IP67/68 Ethernet Switch
- Rackmount Managed Switch
- Gigabit Switch
- Redundant Switch
- Entry-Level Switch
- Networking Computer
- Communication Computer
- Ethernet I/O Server
- Serial Device Server
- Media Converter
- Multiport Serial Card
- SFP Module
- Din Rail Power Supply

Dimensions (Unit –mm)



Specification

Technology

Standard:

IEEE802.3 10Base-T
 IEEE802.3u 100Base-TX
 IEEE802.3ab 1000Base-T
 IEEE802.3z Gigabit Ethernet Fiber
 IEEE802.3x flow control and back pressure
 IEEE802.1p Class of Service

Performance

Switch Technology:

Store and Forward Technology with 32Gbps Switch Fabric.

System Throughput: 14,880pps for 10M Ethernet, 148,800pps for 100M Fast Ethernet, 1,488,100 for Gigabit Ethernet

Transfer packet size: 64 bytes to 1522 bytes (with VLAN Tag)

MAC Address: 8K MAC address table

System Packet Buffer: 1Mbits shared packet buffer

Quality of Service:

Compliance with IEEE802.1p class of service with Tag Based Priority rule Per switch port provides 4 priority queues with 8 (Higher):4(High):2(Low):1(Lower) scheduling. The Tag Priority ID as following: Higher (6,7), High (4,5), Low (0,3), Lowest (1,2)

Interface

Number of Ports:

7 x 10/100 Base-TX with Auto MDI/MDI-X function Auto-Negotiation

3 x 1000Base-T supports Auto MDI/MDI-X , Auto-Negotiation function and combo with Small Form Factor Package (SFP) socket

Connectors:

10/100 Base-TX: RJ-45

1000Base-T: RJ-45

Port # 8, 9 10/100/1000 TX

Port # 10 1000 TX

SFP: supports all 3.3v SFP type Gigabit fiber transceiver

Power: 4-Pin Removable Terminal Block connector

Cables:

RJ-45 connector: supports CAT-3, CAT-4, CAT-5 unshielded twisted pair or shielded twisted pair cable. The link distance is maximum 100 meters

Diagnostic LED:

System Power: Power 1 (Green), Power 2 (Green)
 10/100 Mbps RJ-45 port: Link/Activity (Green), Full Duplex/ Collision (Yellow)
 port: Link/Activity(Green)
 1000Base-T RJ-45 port: Link/Activity (Green)
 SFP port: Link/Activity (Green)

Power Requirements

System Power:

4 pins terminal block for power input.
 DC 24V (12~48V) with polarity reverse protection and redundant function

Power Consumption:

11.5 Watts @ DC 24V(Maximum)

Mechanical

Installation: DIN-Rail or Wall mount

Case:

Aluminum metal case with IP31 grade case protection for drop-waterproof and dustproof

Dimension: 137mm(H) x 96mm (W) x 119mm (D)

Weight:

0.875g without package

Environmental

Operating Temperature: -20 ~70°C

Operating Humidity: 0% ~ 90%, (non-condensing)

Storage Temperature: -40 ~ 85°C

Storage Humidity: 0%~ 95%, (non-condensing)

Hi-Pot: 1.2KV for port and power

Regulatory Approvals

EMI: FCC Class A, CE/EN55022

EMS:

EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-8, EN61000-4-11

Safety: UL/cUL 60950

Shock: IEC60068-2-27

Vibration: IEC60068-2-6

Free Fall: IEC60068-2-32

MTBF: 267380 hours @ 25°C

Warranty: 5 years

Ordering Information

JetNet 3010G Industrial 7+3G Gigabit Ethernet Switch

Includes:

- JetNet 3010G(without SFP transceiver)
- Quick Installation Guide
- CD User's manual

Optional Accessories

Gigabit Multi-Mode SFP Transceiver

Gigabit Single-Mode SFP Transceiver

Gigabit BIDI/WDM Single-Mode SFP Transceiver