

NT24k-DR16 Modular Industrial Switch

N-Tron Ethernet Series



Managed Gigabit Ethernet Industrial Switch

The Red Lion N-Tron NT24k-DR16 is a modular managed switch designed for factory automation, utilities, security surveillance, SCADA and other industrial applications.

The versatile N-Tron® NT24k-DR16 Managed Industrial Ethernet Switch features connectivity for up to 16 Gigabit ports and offers a wide range of connectivity options—including 100Base, Gigabit, fiber optic and copper options—in a rugged DIN rail enclosure. Designed to handle the most demanding environments, the NT24k-DR16 delivers wire-speed throughput and includes expanded shock and vibration tolerances, extreme operating temperature range and two slots to accommodate mix-and-match port modules. N-Ring™ technology restores network communication within ~30ms of fault detection. Robust remote monitoring capabilities make management easy.



APPLICATIONS

- > Factory Automation
- > Utilities
- > SCADA
- > Security Surveillance
- > Transportation
- > Alternative Energy

PRODUCT HIGHLIGHTS

- > All Gigabit Modular Design
- > Up to 16 Port Connections
- > High Environmental Specifications
- > N-Ring Advanced Ring Technology
- > Robust Remote Monitoring
- > Smart Plug-and-Play Operation

FEATURES & BENEFITS

- > Supports up to two of the following port modules:
 - 8-port 10/100/1000BaseT(X) module
 - 8-port 100Base fiber module
 - 8-port 1000Base fiber module
 - 8-port Gigabit SFP module
 - 8-port dual mode SFP module (100Base or 1000Base SFP transceivers)
- > -40° C to 75° C operating temperature
- > Power input selections:
 - Low Voltage: 18-49 VDC
 - High Voltage: 90-264 VAC or 90-300 VDC
- > Onboard temperature sensor
- > ESD and surge protection diodes on all copper ports
- > Auto-sensing 10/100/1000BaseT(X), duplex and MDIX
- > USB configuration port
- > Configurable alarm contact
- > Optional backup/restore configuration device
- > Fully managed features include:
 - Jumbo frame support
 - SNMP v1, v2, v3
 - Web browser management
 - Detailed ring map and fault location charting
 - RSTP - 802.1d, 802.1w, 802.1D
 - IGMP auto-configuration
 - Trunking and port mirroring
 - 802.1Q tag VLAN and port VLAN
 - 802.1p QoS, port QoS and DSCP
 - DHCP client
 - N-Ring technology with ~30ms healing
 - N-View™ OPC monitoring

industrial
networking



Managed Gigabit Ethernet Industrial Switch Specifications

SWITCH PROPERTIES

Number of MAC Addresses: 16K
 Aging Time: Programmable
 Latency (typical): 1.6 µs
 Switching Method: Store & Forward
 MTBF: >1 million hours

POWER INPUT OPTIONS

Select one:
 Low Voltage: 18-49 VDC
 High Voltage: 90-264 VAC or 90-300 VDC
 Input Current (max): 1.52A @ 24VDC
 Input Current (max): 580mA @120 VAC/300mA @ 124VDC
 BTU/hr: 125 @ 24VDC
 BTU/hr: 268 @ 120VAC/127 @ 124VDC

CONNECTORS

10/100/1000BaseT(X): Up to 16 RJ45 copper ports
 100BaseFX: Up to 16 SC or ST fiber ports
 1000BaseGX: Up to 16 SC fiber ports
 100BaseSX/LX SFP: Up to 16 LC fiber ports
 1000BaseGX SFP: Up to 16 LC fiber ports

RELIABILITY

MTBF: >1 million hours

NETWORK MEDIA

10BaseT: ≥Cat3 cable
 100BaseTX: ≥Cat5 cable
 1000BaseT: ≥Cat5 cable
 100BaseFX, 1000BaseSX Multimode: 50-62.5/125µm
 100BaseFXE, 1000BaseLX Singlemode: 7-10/125µm

RECOMMENDED WIRING CLEARANCE

Front and Top: 4" (10.2 cm)

SUBMITTED FOR TESTING

Product Safety:
 Class I, Division 2, Groups A, B, C and D hazardous locations
 UL508
 ANSI/ISA 12.12.01-2011
 CAN/CSA-C22.2 No. 14-01
 CAN/CSA-C22.2 No. 213-M1987
 Emissions: FCC Title 47, Part 15, Radio Frequency Devices, Subpart B
 ANSI C63.4-2009; Industry Canada ICES-003
 EN 55011; EN 61000-6-4 (radiated and conducted)
 Immunity: EN 61000-3-2; EN61000-3-3; EN 61000-6-2; IEC 61000-4-2 (ESD); IEC 61000-4-3 (RFAM); IEC 61000-4-4 (EFT); IEC 61000-4-5 (SURGE); IEC 61000-4-6 (RFCM); IEC 61000-4-8 (PFMF); IEC 61000-4-11 (VDI)
 Other: EMC Directive 2004/108/EC; GOST-R


ENVIRONMENTAL

Operating Temperature: -40° C to 75° C
 Operating Humidity: 5% to 100% (Non Condensing)
 Operating Altitude: 0 to 10,000 ft.
 Shock: 50g @ 10ms
 Vibration/Seismic: 30g, 10-200 Hz, triaxial

MECHANICAL

Case Dimensions
 Height: 5.97" (15.20 cm)
 Width: 6.78" (17.22 cm)
 Depth: 4.59" (11.65 cm)
 Weight (maximum): 6.4 lbs (2.9 kg)
 Mount: DIN rail

DIMENSIONS



All specifications are subject to change. Consult the company website for more information.

ORDERING GUIDE

PART NUMBER	DESCRIPTION
NT24K-DR16-DC	Managed Industrial Ethernet Switch; modular DIN rail design with 2 expansion slots; redundant 18-49VDC power input
NT24K-DR16-AC	Managed Industrial Ethernet Switch; modular DIN rail design with 2 expansion slots; 90-264VAC / 90-300VDC power inputs
NT24K-FP	Filler panel (required to fill vacant module slots)
NTCD-CFG	Configuration recovery device
NTPC-AC-US	AC power cord
NTPS-24-3	DIN rail power supply 3.0 Amp@24 VDC
NT24K-DR-PMK	NT24k DR panel mount kit

PORT MODULES & TRANSCEIVERS

NT24K-TX8	8-port 10/100/1000BaseT module
NT24K-FX8-XX	Slide-in module with 8 100BaseFX multimode fiber ports, 2km (SC or ST)
NT24K-FXE8-XX-YY	Slide-in module with 8 100BaseFX singlemode fiber ports (SC or ST)
NT24K-GX8-SC	Slide-in module with 8 1000BaseFX multimode fiber ports, 550m (SC)
NT24K-GXE8-SC-ZZ	Slide-in module with 8 1000BaseFX singlemode fiber ports (SC)
NT24K-SFP8	Slide-in module with 8 SFP expansion slots; supports 1000Base SFP transceivers*
NT24K-SFP-DM8	Slide-in module with 8 dual mode SFP expansion slots; supports 100Base or 1000Base SFP transceivers*
NTSFP-FX	100BaseFX multimode fiber SFP pluggable mini-GBIC transceiver (LC style connector, 2km)**
NTSFP-FXE-YY	100BaseFX singlemode fiber SFP pluggable mini-GBIC transceiver (LC style connector)**
NTSFP-TX	1000BaseT copper SFP pluggable mini-GBIC transceiver
NTSFP-SX	1000BaseSX multimode fiber SFP pluggable mini-GBIC transceiver
NTSFP-LX-ZZ	1000BaseLX singlemode fiber SFP pluggable mini-GBIC transceiver

Where: XX = ST or SC connector (ST not available on some GX modules); YY = 15, 40, or 80 for FX singlemode, blank for multimode; ZZ = 10, 40, or 80 for GX singlemode; *SFP transceivers sold separately; **For use with SFP DM8 module only



www.redlion.net

Connect. Monitor. Control.

Americas
 sales@redlion.net

Asia-Pacific
 asia@redlion.net

**Europe
 Middle East
 Africa**
 europe@redlion.net

+1 (717) 767-6511

As the global experts in communication, monitoring and control for industrial automation and networking, Red Lion has been delivering innovative solutions for over forty years. Our award-winning technology enables companies worldwide to gain real-time data visibility that drives productivity. Product brands include Red Lion, N-Tron and Sixnet. With headquarters in York, Pennsylvania, the company has offices across the Americas, Asia-Pacific and Europe. For more information, please visit www.redlion.net. Red Lion is a Spectris company.