

FWA8108

Mainstream LGA1155 3rd Generation Intel® Core™ i7/i5/i3 / Xeon® Network Appliance w/ 8 GbE Ports



Specifications

CPU	LGA1155 for Intel® 3rd Generation Core™ i7/i5/i3 / Xeon® processors
Chipset	Intel® C216 PCH chipset
Memory	4x DDR3 DIMMs Max. 32GB, up to 1600 MHz ECC or non-ECC (depending on CPU)
LAN	1x Intel® 82579LM GbE PHY w/ iAMT 8.0 support 7x Intel® 82583V GbE, w/o Bypass
Expansion Slot	1x Mini PCI-E (mSATA compatible) socket 2 slots opening on rear panel
Storage	2.5" / 3.5" HDD drive bay support 1x CF socket
USB	2x USB 3.0 port on front panel
Serial I/O	1x RJ45 console, COM2 pin header
VGA	Pin header
LED	Power / Status
Power Supply	Full range 300W ATX
Dimensions	440 mm (W) x 411.5 mm (D) x 44 mm (H) 17.3"(W) x 16"(D) x 1.73"(H)
Operating Temperature	0°C ~ 45°C (32°F ~ 113°F)
Storage Temperature	-20° ~ 70°C (-4°F ~ 158°F)
Operating Humidity	5 ~ 90%
Certification	CE/FCC

Features

- Supports Intel® 3rd Generation Core™ i7/i5/i3 / Xeon® processors
- 8x PCI-E GbE ports
- 4x DDR3 DIMMs, Max. 32 GB
- 3x System smart fans
- 1x CF socket, 1x Mini PCI-E slot (mSATA compatible)
- iAMT 8.0

Ordering Information

FWA8108	FWA 1U 19" Rackmount Appliance, MB967-FT, supports LGA1155 CPUs, GbE x8, 300W PSU, CPU cooler, 2.5" / 3.5" HDD bracket, IP333, w/o Bypass
MB967-FT	LGA1155 for 3rd Generation Core™ i7/i5/i3 / Xeon®, C216 PCH, 1x Intel® GbE 82579LM + 7x Intel® GbE 82583V, SATA connector, Mini PCI-E, CF & PCI-E expansion, w/o Bypass
VGA4	VGA cable
IP333	2-to-2 PCI-E 8x riser card
PK1-51	Console cable, 160cm
USB2-7	Dual Port USB 2.0 cable, 300mm

Dimensions

