

# TN-5305 Series

## EN 50155 5-port IP67 unmanaged Ethernet switches



- > 10/100BaseT(X), 4-pin M12 (D-coding), F/H duplex mode, and auto MDI/MDI-X connection
- > IP67 rated housing protection
- > Power input: 12 to 45 VDC, 18 to 30 VAC
- > Compliant with essential sections of EN 50155
- > -40 to 75°C operating temperature range (T models)



### Introduction

The TN-5305 series Ethernet switches are IP67 rated for the toughest industrial applications, which means that the rugged housing and connectors guard against dust, water, and oil. By using M12 connectors, you can rest assured that Ethernet cables will connect tightly to the switch, and will be robust enough to protect your applications from external disturbances, such as the vibration and shock encountered in the transportation industry. The space-saving

TN-5305 switches can be mounted virtually anywhere, and wide operating temperature (-40 to 75°C) models are also available for use in the extremest of conditions. The TN-5305 Series Ethernet switches are compliant with the essential sections of EN 50155, covering operating temperature, power input voltage, surge, ESD and vibration, making the switches suitable for a variety of industrial applications.

### Specifications

#### Technology

##### Standards:

IEEE 802.3 for 10BaseT  
IEEE 802.3u for 100BaseT(X)  
IEEE 802.3x for Flow Control

**Processing Type:** Store and Forward

**Flow Control:** IEEE 802.3x full duplex, back pressure flow control

##### Interface

**M12 Ports:** 10/100BaseT(X) auto negotiation speed, F/H duplex mode, and auto MDI/MDI-X connection

**LED Indicators:** Power, LNK/ACT

#### Power Requirements

##### Input Voltage:

- 24 VDC (12 to 45 V)
- 18 to 30 VAC (47 to 63 Hz)

**Note:** Compliant with EN 50155 on 24 VDC

##### Input Current:

- 0.12A @ 24 VDC
- 0.28A @ 24 VAC

**Overload Current Protection:** 1.1 A (Limited Current)

**Connection:** 1 M12 socket (A-coding), single power input

**Reverse Polarity Protection:** Present

#### Physical Characteristics

**Housing:** Plastic, IP67 protection

**Dimensions:** 60 x 125 x 29.6 mm (2.36 x 4.92 x 1.09 in)

**Weight:** 250 g

**Installation:** Field-style mounting, DIN-Rail mounting (with optional kit)

#### Environmental Limits

##### Operating Temperature:

Standard Models: -25 to 60°C (32 to 140°F)  
Wide Temp. Models: -40 to 75°C (-40 to 167°F)

**Storage Temperature:** -40 to 85°C (-40 to 185°F)

**Ambient Relative Humidity:** 5 to 95% (non-condensing)

#### Standards and Certifications

**Safety:** UL 508

**EMI:** FCC Part 15 Subpart B Class A, EN 55022 Class A

##### EMS:

EN 61000-4-2 (ESD) Level 3,  
EN 61000-4-3 (RS) exceeds Level 3,  
EN 61000-4-4 (EFT) Level 3,  
EN 61000-4-5 (Surge) Level 3,  
EN 61000-4-6 (CS) Level 2,  
EN 61000-4-8,  
EN 61000-4-11

**Rail Traffic:** (for panel mounting installations)

EN 50155, EN 50121-4 (Pending)

**Shock:** IEC 60068-2-27

**Freefall:** IEC 60068-2-32

**Vibration:** IEC 60068-2-6

**Note:** Please check Moxa's website for the most up-to-date certification status.


#### Warranty

**Warranty Period:** 5 years

**Details:** See [www.moxa.com/warranty](http://www.moxa.com/warranty)

## Dimensions

Unit: mm (inch)



## Ordering Information

Available Models		Port Interface
Standard Temperature (-25 to 60°C)	Wide Temperature (-40 to 75°C)	10/100BaseT(X), M12 connector
TN-5305	TN-5305-T	5

Note: Comformal coating is available on request.

### Optional Accessories (can be purchased separately)

**DR-4524/75-24/120-24:** 45/75/120 W DIN-Rail 24 VDC power supplies

**Power Cords, M12 Connectors, Protective Caps:** See page 2-22

**DK-M12-305:** DIN-Rail mounting kit

### Package Checklist

- TN-5305 switch
- 3 protective caps for unused ports and 8 port labels
- Panel mounting kit
- Documentation and software CD
- Hardware installation guide
- Warranty card

# Accessories

## : M12/M23 Power Cords

### **CBL-M12D(MM4P)/RJ45-100 IP67**

1-meter M12-to-RJ45 Cat-5C UTP Ethernet cable with IP67-rated 4-pin male D-coded M12 connector



### **CBL-M12(FF5P)/OPEN-100 IP67**

1-meter M12-to-5-pin power cable with IP67-rated 5-pin female A-coded M12 connector



### **CBL-M23(FF6P)/Open-BK-100 IP67**

1-meter M23-to-6-pin power cable with IP67-rated 6-pin female M23 connector



## : M12 Connectors

### **M12D-4P-IP68**

Field-installable M12 D-coded screw-in sensor connector, 4-pin male, IP68-rated



### **M12A-5P-IP68**

Field-installable M12 A-coded screw-in sensor connector, 5-pin female, IP68-rated



## : M12 IP67 Protective Caps

### **A-CAP-M12F-M**

Metal cap for M12 female connector



### **A-CAP-M12M-M**

Metal cap for M12 male connector



## : M23 Connectors

### **A-PLG-WPM23-01**

M23 cable connector, 6-pin female, crimp type

