



TC-NT2 Professional Cable Tester with Tone Generator

The TC-NT2 is a convenient and comprehensive cable tester for network professionals. Its powerful and user-friendly features enable network installers to accurately check pin configurations of various voice and data communication cables. The TC-NT2 includes a master unit that transmits test signals to its corresponding remote terminator to verify cable reliability. It checks continuity and displays wiring configuration up to 300 meters of cable installation. With the unique feature of the audio tone generator, the TC-NT2 identifies and troubleshoots faulty cables to assure proper pin and wiring structure.



Features

- Tests Pin Configuration of 10/100/1000Base-T, 10Base-2 (coax), RJ-11/RJ-12/RJ-45, EIA/TIA-356A/568A/568B, and Token Ring Cables
- Tests USB and IEEE 1394 cables with optional adapters
- Built-in Tone Generator for tracing cable with standard Tone Probe
- Tests the grounding on shielded (screened) cable
- Verifies cable continuity, opens, shorts, and miswires
- Tests cable up to 300 meters
- Auto-Scan or Manual-Scan mode
- Includes Deluxe Carrying Pouch, two RJ45-to-BNC Adapters, and RJ45 Patch Cable
- 1-year warranty

Specifications

- Power Requirement:** One DC 9V battery
- Tone Frequency:** 600 ~ 800 Hz.
- Dimensions (appr.):** Master Unit: 115 x 68 x 27 mm (4.5 x 2.7 x 1.1 inch)
- Remote Terminator:** 118 x 32 x 27 mm (4.6 x 1.3 x 1.1 inch)
- Operating Temp:** 0° C ~ 45° C (32° F ~ 113° F)
- Weight (appr.):** Master Unit: 113 gram (4 Oz.) (without battery)
- Remote Terminator:** 57 gram (2 Oz.)

RELATED PRODUCT

- **TC-NT2**
Network Cable Tester with Tone Generator for UTP, STP, Coaxial, and Modular Cables
- **TC-CT68**
RJ-11/RJ-45 Crimp/Cut/Strip Tool
- **TC-PDT**
Punch Down Tool with 110 and Krone Blade
- **TC-1KC5G**
100MHz CAT 5 Solid Cable/1,000 Feet Box

ORDERING INFORMATION

TRENDware International, Inc.
3135 Kashiwa Street
Torrance, CA. 90505. USA
Tel: 310-891-1100
Fax: 310-891-1111
Web: www.TRENDNET.com
Email: sales@trendware.com

**To Order Please Call:
1-888-326-6061**