Digi CM™

Console Server

The Digi CM offers secure, reliable in- and out-of-band management for servers, routers, switches, firewalls and other network equipment.



Overview

The Digi CM provides secure access to any network device, even when the network is down. Users can monitor and control their devices from anywhere using the corporate TCP/IP network, the Internet or dial-up modem connections. This easy-to-use console management tool is ideal for managing servers, routers, switches and any network device with a serial port.

Automatic Device Recognition auto-configures attached devices and populates the Title page with device details. This feature monitors the ports and sends alerts for disconnected or down devices.

The RemotePorts[™] feature enables cost-effective management of up to 48 additional remote devices from a single interface. Additional devices can be managed from the Digi CM using an auxiliary device or terminal server, or from across the network.

The Digi CM, used in conjunction with the Digi Remote Power Manager, offers comprehensive infrastructure management. Users can remotely power on/off connected devices, reboot servers, and receive notifications of changes in power usage, temperature readings, system reboots and more.



Application Highlight Remote Administrator **Local Network** Headquarter LAN Analog PSTN 10/100 BT Corporate LAN Modem Digi CM Sun Netra Cisco Router Sun Netra PBX Sun Netra rial Connections to Console Ports Features/Benefits

- Sun, Cisco, IBM, HP, UNIX®, Linux® and Microsoft Windows Server® 2003 compatible
- TACACS+, RADIUS, LDAP, Kerberos, local user database provide centralized authentication
- SSH v2 ensures secure access
- Secure clustering allows multi-server access via one IP address
- Port buffering/logging for easy troubleshooting
- Straight-through CAT5 cabling for easy, hassle-free server connections
- PC Card slot for increased flash, or additional Ethernet/modem connection
- Email/pager alerts and SNMP traps



Platform	Digi CM™ 8	Digi CM™ 16/32	Digi CM™ 48	
Features				
Authentication	TACACS+, RADIUS, LDAP, Kerberos, Local user database			
Security	SSHv2 server and client, SSL, IP filtering, Data capture via port buffering			
Management	Command Line, We	Command Line, Web (HTTP/HTTPS), SNMP, Multi-level menuing, Port triggers and alerts		
Operating Systems		Embedded Linux (Hard Hat Distribution)		
Connections		Standard CAT5 cabling for RJ-45 serial ports		
Port Access	Telnet/SSH with menuing, Reverse Telr	Telnet/SSH with menuing, Reverse Telnet/SSH, HTTP/HTTPS, Multiple users per port, SSH sessions simultaneously on all ports, IP addresses per port		
Supported PC Cards	CompactFlash memory card, W	CompactFlash memory card, Wireless LAN adapter (802.11b), Ethernet LAN adapter, PSTN/CDMA modem card		
Rack Mount	19" rack mount kit included			
Memory	64 MB SDRAI	64 MB SDRAM, 8 MB Flash 256 MB SDRAM,		
Dimensions (L x W x D)	9.50 in x 6.25 in x 1.25 in (24.10 cm x 15.90 cm x 3.20 cm)	17.00 in x 8.50 in x 1.75 in (43.20 cm x 21.60 cm x 4.50 cm)	17.50 in x 10.00 in 1.75 in (44.50 cm x 25.40 cm x 4.50 cm)	
Weight	2.50 lb (1.10 kg)	5.80 lb (2.60 kg)	6.40 lb (2.90 kg)	
Interfaces				
Serial Ports	8 RJ-45 RS-232	16 or 32 RJ-45 RS-232	48 RJ-45 RS-232	
Console Ports	1 RJ-45 RS-232			
Ethernet Ports	1 RJ-45 10/100Base-T			
PC Card Slot		One 16-bit PCMCIA		
Power Requirements				
Power Supply	External 100-240VAC, 50/60 Hz, 12 W max, 6 W typical	Internal 100-240VAC, 50/60 Hz, 40 W max, 12 W typical		
Power Supply MTBF		11 years		
Environmental				
Operating Temperature	5° C to 50° C (41° F to 122° F)			
Storage Temperature		-30° C to +60° C (-20° F to +140° F)		
Regulatory Approvals				
Safety		UL 1950, EN60950		
Emissions/Immunity	CE,	CE, FCC Part 15 (Class A), EN55024, EN55022 (Class A)		



PIN SIGNAL 1 CTS 2 DSR RxD

SAFETY GND

4 5 DCD 6 TxD

DTR







Visit www.digi.com for part numbers.

Digi International

DIGI SERVICE AND SUPPORT - You can purchase with confidence knowing that Digi is here to support you with expert technical support and a strong five-year warranty. www.digi.com/support

91001129 J1/509

Digi International

877-912-3444 France 952-912-3444 +33-1-55-61-98-98 info@digi.com www.digi.fr

Digi International KK

+81-3-5428-0261 www.digi-intl.co.jp **Digi International** (HK) Limited

+852-2833-1008 www.digi.cn

BUY ONLINE • www.digi.com

