


AQUAFOG



Image of High capacity fogging output of an HRSM unit



AquaFog® - Mobile Fogging Units

These highly desirable stand-alone atomizing unit are available in three different versions.

- **HRSM** - designed for general applications requiring high quality fogging outputs for either Humidification and/or Evaporative Cooling applications.
- **ORSM** - designed for the Odor Control Industry. This unit allows for an connection to a metering pump supply, for atomizing Odor Control product.
- **CRSM** - designed for fogging Pesticide, Fungicides. This unit has an internal agitation system for keeping powered or liquid chemicals well stirred for un-manned fumigation applications.

SPECIFICATIONS:

Dimensions: Length 25.5 inches / 65 cm
Width 21 inches / 53 cm
Height 44 inches / 112 cm

Approximate Weight: 80 lbs / 36.3 kg
Approximate Shipping Weight: 127 lbs / 57.6 kg
Fogging Head Pivot Angle: 0°, 15°, 30°, 45°
Noise @ 10 ft. distance: 1 Hp units, 76-79 dB(A)
3/4 Hp units, 73-76 dB(A)
1/2 Hp units, 74-77 dB(A)

Tank Capacity: 18 U.S. Gallons / 68 Liters
Main Motor (Standard): Baldor® Wash Down Duty™
Thermo-plastic Material: UV Stabilized Polyethylene
Hardware: 18-8 (304 Stainless Steel)
Operation: Continuous duty capability



Standard Features:

- All the ..RSM units are supplied with a four (4) position adjustable fogging head
- Large tank holds up to 18 US gallons (68 liters)
- Equipped with flow control, automatic fill float-valve assembly, water hose connection and fluid level gauge.
- Engineered for harsh indoor/outdoor environments, units have all stainless steel hardware and heavy wall thermo-plastic construction.
- Wide-mouth opening for adding chemicals
- Drain plug for easy cleaning
- Sturdy molded handles and 10" semi-pneumatic wheels for rugged mobility.
- Features no-clog, nozzle-free atomization head
- Delivered fully assembled, ready for operation



**C
R
S
M**

AQUAFOG

CHEMICAL

RECIRCULATION

SUMP

MODULE



AquaFog® CRSM™
- Mobile Chemical Fumigation

CRSM's are specially designed for chemical applications (ULV). Units have an internal agitation system mixtures thoroughly stirred during the fogging operation. wettable powers as well as liquid additives to be incorporated into the system. CRSM's are enormously powerful with a pivoting fogging head allowing you to propel the vapor way-up high for superior coverage and circulation. Units produce billions of tiny fog particles for treating greenhouses or similar enclosed areas from 3,000 to 30,000 sq. ft. from a single location. Compact, sturdy and easy to maneuver from location to location, systems are designed for unmanned operation and are supplied with an automatic timer control.

AquaFog® CRSM™ mystifies the competition; but don't let CRSM's affordable price tag fool you, these units are top quality and built like a tank. Our advanced, innovative technology gives AquaFog® it's decisive edge over the big names. Well back this up with a rock solid 30 day money-back guarantee if your not completely satisfied in any way.

Loaded with features - no-clog, nozzle-free 4 position pivoting atomizing head, flow control valve, automatic priming system, fluid level gauge, timer control package, and simplified dilution and spraying charts. Construction is UV stabilized, with watertight electrical enclosures & connections and all stainless steel hardware. CRSMs arrive fully assembled and ready for operation. Delivered by common carrier.

Made in
 U.S.A.

fumigation applica-
 that keeps chemical

This powerful agitation allows the use of heavy wettable powers as well as liquid additives to be incorporated into the system. CRSM's are enormously powerful with a pivoting fogging head allowing you to propel the vapor way-up high for superior coverage and circulation. Units produce billions of tiny fog particles for treating greenhouses or similar enclosed areas from 3,000 to 30,000 sq. ft. from a single location. Compact, sturdy and easy to maneuver from location to location, systems are designed for unmanned operation and are supplied with an automatic timer control.



CRSM comes with a timer control package

	Model Number	Motor Size	Electrical Rating	Fog output	CFM
Domestic Voltage	XE-CRSM-1000	1/2 HP	115V 60Hz 1Ph	Up to 5 GPH	2,730
Foreign	XE-CRSM-1500	3/4 HP	240V 50Hz 1Ph	Up to 5 GPH	3,180