



Power Supply Kits

24VDC External Power Adapter

Terminal (24V, 24W, 3-Pin)

This power supply kit includes a 24-watts Universal AC-DC switching power supply and power cords that are compatible with North American and European standards. The power supply outputs 24VDC and operates in the range of 90 to 264VAC, 47-63Hz. The power supply has a 3-pin Terminal Block output connector built into it. This enables users to provide power to Control DeviceMaster products without the need of any wiring. In addition, the power supply operates in the extended temperature range of -37°C to 74°C, which enables users to use the power supply in harsh environment.



Part Number
1200036

5VDC External Power Adapter

Barrel Power (5VDC, 15W, 2.1MM Barrel Connector)

This power supply consists of a 5VDC, 15 Watts Universal AC-DC desktop power supply and power cords that are compliant with North American and European power cord standards. The power supply outputs 5VDC and operates in the input voltage range of 90-264VAC, 47-63Hz. The power supply has a 2.1MM diameter Barrel connector. It powers Control DeviceMaster RTS, 1 Port, DB9M, 5VDC products. In addition, it is a ruggedized power supply rated to operate in the extended temperature range of -37°C to 74°C. This enables users to power products in harsh environments with extreme temperatures. The power supply has a green status LED to display its proper operation.



Part Number
1200037



24VDC External Power Adapter

Bare Wires(24VDC, 24W, 3-Wire)

This universal power supply kit consists of a 24 Watts Universal AC-DC power supply and power cords that are compliant with North American and European power cord standards. The power supply outputs 24VDC and operates in the input voltage range of 90-264VAC, 47-63Hz. The power supply has three stripped and tinned bare output wires enabling users to simply connect wires to power products with terminal block inputs. Additionally, the power supply operates in the extended temperature range of -37°C to 74°C enabling users to power products in harsh environments. The power supply has a green status LED to display its proper operation.

Wire codes and functionality

Red is 21-27 VDC +
White is 21-27VDC - (common)
Black is chassis (earth) ground

Part Number
1200038



48VDC External Power Supply Adapter

Bare Wires (48VDC, 120W, 2-Wire)

This 48V power supply supports up to 120W meeting the high power demands of the RocketLinx managed PoE Ethernet Switches. It includes bare wire leads for direct connection to the power terminal blocks of the RocketLinx switches. It is a universal power supply that supports 110V or 230VAC and includes both US and EU AC power cords.

Part Number
1200048



PRODUCT SUPPORT & SERVICE INFORMATION

Warranty Information

Comtrol offers a 30-day satisfaction guarantee and 5-year limited warranty.

Sales Support

+1.763.957.6000
sales@comtrol.com

Technical Support

+1.763.957.6000
www.comtrol.com/support

Email, FTP, and Web Support

info@comtrol.com
ftp.comtrol.com
www.comtrol.com