



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: PDUMV15

**Single-Phase Metered PDU, 15A 120V, 0U Vertical Rackmount, NEMA 5-15R outlets, NEMA 5-15P input plug**



### Highlights

- Digital current meter display
- 16 outlets
- Convenient and safe covered on/off switch
- 15 amp breaker
- 15-ft. cord
- 48" length
- Toolless button mounting

### Description

PDUMV15 48 inch / 122cm vertical 0U metered rack PDU supports 15A maximum capacity at 120V. Includes 15 ft / 4.6m line cord with 5-15P input plug. 16 NEMA 5-15R outlets. Built-in 2 character digital current display.

Tripp Lite Metered Power Distribution Units give IT Managers the ability to monitor network power consumption levels to prevent mains, generator, UPS or PDU overloads and to ensure proper load balance in complex redundant power applications. Each built-in, easy to read, two-character LED display offers continuous PDU current monitoring data in one-amp increments. Switch-free unfiltered electrical pass-through reliably distributes UPS or generator power to multiple servers and vital networking equipment in rack enclosures, network closets and more. Toolless mounting enables simple installation in button-mount compatible racks. Included mounting brackets support vertical installation in standard 2 and 4 post racks or other surfaces, such as under-counter or wallmount configurations.

### Applications

- Ideal for horizontal or vertical raceway style metered power distribution in office, workbench, industrial, networking, and telecom applications.

### Package Includes

- PDUMV15 Metered Vertical PDU
- Mounting hardware and spare mounting buttons
- 6 outlet safety covers
- Owner's manual with warranty information

### Features

- 120V 15A Metered Power Distribution Unit (PDU) in 48 inch / 122cm 0U vertical form factor
- 15A maximum capacity
- 15 ft. / 4.5m line cord with 5-15P input plug
- 16 NEMA 5-15R output receptacles
- Outlets are arranged in a single metered 15A load bank
- Current meter offers the ability to monitor network power consumption levels to prevent mains, generator, UPS or PDU overloads and to ensure proper load balance in complex redundant power applications
- Easy to read, two-character LED display offers continuous whole-PDU current monitoring data in one-amp increments
- Toolless installation supports fast installation in button-mount compatible equipment racks
- Included nut & bolt mounting brackets support installation in racks or other flat surfaces, such as under-counter, wallmount and other surfaces
- Lifetime warranty

## Specifications

OVERVIEW	
Model Type	Metered
PDU Type	Metered
OUTPUT	
Frequency compatibility	50 / 60 Hz
Output VA	1800
Output nominal voltage	120V
Overload protection	15A
Outlet quantity / type	16 NEMA 5-15R
INPUT	
PDU Input Voltage	100; 120; 127
Recommended Electrical Service	120V
Maximum Input Amps (A)	15
Input connection type	NEMA 5-15P
Plug Type	NEMA 5-15P (15A 120V)
PDU Plug Type	NEMA 5-15P
Input cord length (ft.)	15
Voltage compatibility (VAC)	120
Phase	Single-Phase
LEDS ALARMS & SWITCHES	
Switches	Lighted on/off switch with integrated safety cover
Front panel LEDs	Digital LED current monitor display
PHYSICAL	
Shipping weight (lbs)	4.2
Unit Dimensions (HWD/in)	3 x 48 x 1.5
Shipping Dimensions (HWD/in)	51.5 x 3.5 x 2.5
Unit weight (lbs)	3.8
Material of construction	Aluminum
Style	Vertical Rackmount, Wallmount, Raceway, Workbench
Form factors supported	Vertical (0U) mounting in rack enclosures, horizontal mount in raceways and a variety of other applications
PDU Form Factor	Vertical (0U)
SPECIAL FEATURES	
Appearance	Black housing with digital current meter display
CERTIFICATIONS	

<b>Certifications</b>	Tested to UL60950-1 (USA) and CAN/CSA C22.2 No. 60950-1-03 (Canada), RoHS Compliant
<b>WARRANTY</b>	
<b>Product Warranty Period (U.S., Canada &amp; Puerto Rico)</b>	Lifetime limited warranty

## Related Items

### Optional Products

Product Type	Related Model	Description	Qty.
Power Cables	<a href="#">P002-002</a>	2-ft. Power Cord (IEC-320-C14 to NEMA 5-15R)	1
Power Cables	<a href="#">P007-002</a>	2-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to NEMA 5-15P)	1
Power Cables	<a href="#">P007-006</a>	6-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to NEMA 5-15P)	1
Power Cables	<a href="#">P007-010</a>	10-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to NEMA 5-15P)	1
Power Cables	<a href="#">P010-012</a>	12-ft. 18AWG Power cord (NEMA 5-15P to IEC-320-C13)	1
Power Cables	<a href="#">P012-006</a>	6-ft. Notebook Power cord (NEMA 1-15P to IEC-320-C7)	1
Power Cables	<a href="#">P022-001</a>	1-ft. 18AWG Power Extension cord (NEMA 5-15R to NEMA 5-15P)	1
Power Cables	<a href="#">P023-001</a>	1-ft. 14AWG Power Adapter cord (NEMA L5-15R to NEMA 5-15P)	1
Power Cables	<a href="#">P034-010</a>	10-ft. 14AWG Heavy Duty Power cord (IEC-320-C19 to NEMA 5-15P)	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=3458](http://www.tripplite.com/en/products/model.cfm?txtModelID=3458).

Copyright © 2011 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.