



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: PDUMH15AT

**Single-Phase Auto Transfer Switch / Metered PDU, 15A 120V, 1U Horizontal Rackmount, NEMA 5-15R outlets, 2 NEMA 5-15P inputs**

### Highlights

- Single phase 15A 120V Auto Transfer Switch / ATS PDU
- Enables redundant-power option for single-corded network devices
- Separate primary & secondary inputs connect to any two compatible power sources
- 1U horizontal rackmount; 2 NEMA 5-15P inputs; 8 NEMA 5-15R outlets
- Two digit visual current meter; Upgrade options available



### Description

Tripp Lite Metered ATS / Auto Transfer Switch provides a redundant power option for single-corded network devices. Dual input cords support separate connection to PRIMARY and SECONDARY power sources. The ATS will normally maintain continuous output to all outlets as derived from the primary input cable. If the primary power source becomes unstable or fails altogether, the ATS will switch over to the secondary power source until the primary input is restored and stable. Super-fast switchover between primary and secondary power sources occurs within milliseconds. ATS functionality is supported by any two compatible AC power sources, regardless of phase angle, to support a variety of advanced redundant power networking applications. Enables fault tolerant hot-swappable UPS protection when used with a single UPS and fully redundant UPS protection when each cord is connected to a separate UPS system. In a two-UPS environment, the primary input cable must be supported by a full time sine wave UPS with zero transfer time. Tripp Lite SmartOnline series is highly recommended for use as the primary UPS in a two-UPS application. ATS configurations utilizing separate mains circuits, backup generators and even separate utility power grid feeds are fully supported. On-board ATS processor constantly evaluates power quality on both input sources to prevent transfer to the secondary source when unavailable or of lower quality than the primary source. Front input LED's display primary or secondary power availability.

#### Applications

- Ideal means to provide single-corded network gear a redundant power option

#### Package Includes

- PDU with attached 5-15P primary input cord
- Detachable C13 to NEMA 5-15P 12 ft / 3.6m secondary input cord
- 1U mounting brackets
- User manual with warranty information

### Features

- 120V 15A Automatic Transfer Switch (ATS) / Metered PDU (Power Distribution Unit)
- Provides a redundant power option for critical networking equipment with a single input power cord
- 2 digit display reports output power consumption in amps
- 1U horizontal rackmount form factor; 14.5 in. / 36.8 cm depth
- 8 built-in NEMA 5-15R outlets
- Set of two 12 ft. / 3.6m NEMA 5-15P input cables support connection to separate PRIMARY and SECONDARY power sources
- ATS circuits normally maintain output sourced from the primary input cable; As primary input power fails or becomes unstable, the ATS will switch to maintain output sourced from the secondary input cable until power on the primary input is restored and stable
- ATS configurations enable fault-tolerant, hot-swappable UPS protection when used with a single UPS and fully redundant UPS protection when each cord is connected to a separate UPS system (in a two-UPS environment, the primary input cable must be supported by an online UPS with zero transfer time similar to Tripp Lite SmartOnline series)

- Advanced ATS configurations utilizing separate mains circuits, backup generators and even separate out of phase utility power grid feeds are fully supported
- On-board ATS processor constantly evaluates power quality on both inputs to prevent transfer to the secondary source when unavailable or of lower quality than the primary source
- Super-fast switchover between primary and secondary power sources occurs in 2-7 milliseconds
- Built-in card slot supports optional SNMPWEBCARD for permanent upgrade to a switched & monitored PDU system
- Outlets are factory programmed for sequential turn-on at 250 millisecond intervals when the PDU is first energized to prevent inrush-related equipment interaction on startup
- Front panel LEDs confirm power availability on both input lines

## Specifications

OVERVIEW	
Model Type	ATS/Auto Transfer Switches; Metered
PDU Type	Auto-Transfer Switch; Metered
OUTPUT	
Frequency compatibility	60 Hz
Output VA	1800
Output nominal voltage	120V
Outlet quantity / type	8 NEMA 5-15R
INPUT	
PDU Input Voltage	100; 120; 127
Recommended Electrical Service	120V
Maximum Input Amps (A)	15
Input connection type	2 NEMA 5-15P
Plug Type	NEMA 5-15P (15A 120V)
PDU Plug Type	NEMA 5-15P
Input cord length (ft.)	12
Voltage compatibility (VAC)	120
Phase	Single-Phase
LEDS ALARMS & SWITCHES	
Front panel LEDs	10 front panel LEDs display power on - off status for each outlet, plus 3 LEDs for power status on each input line cord. Digital Current Meter displays output power consumption in amps.
PHYSICAL	
Shipping weight (lbs)	15.2
Shipping weight (kg)	6.9
Unit Dimensions (HWD/in)	1.75 (1U) x 17.5 x 14.5
Unit Dimensions (HWD/cm)	4.44 x 44.4 x 36.8

<b>Shipping Dimensions (HWD/in)</b>	6.25 x 22.5 x 23.5
<b>Shipping Dimensions (HWD/cm)</b>	15.9 x 57.2 x 59.7
<b>Unit weight (lbs)</b>	11
<b>Unit weight (kg)</b>	5
<b>Material of construction</b>	Steel
<b>Style</b>	Rackmount
<b>Form factors supported</b>	1U rackmount
<b>PDU Form Factor</b>	Horizontal (1U, 2U, etc)
<b>ENVIRONMENTAL</b>	
<b>Relative Humidity</b>	Up to 95% (non-condensing)
<b>COMMUNICATIONS</b>	
<b>SNMP compatibility</b>	Includes slot for optional <a href="#">SNMPWEBCARD</a> accessory to enable remote individual outlet control over IP
<b>SPECIAL FEATURES</b>	
<b>Appearance</b>	Black 1U rackmount steel chassis
<b>CERTIFICATIONS</b>	
<b>Certifications</b>	Tested to UL 60950-1 (USA), CSA (Canada), Class A (Emissions), NOM (Mexico), RoHS compliant
<b>WARRANTY</b>	
<b>Product Warranty Period (U.S., Canada &amp; Puerto Rico)</b>	2-year limited warranty

## Related Items

### Optional Products

Product Type	Related Model	Description	Qty.
Extended Warranties	<a href="#">WEXT3-PDU-AT</a>	3-Year Extended Warranty - For PDUMH15AT and PDUMH20AT only	1
Extended Warranties	<a href="#">WEXT5-PDU-AT</a>	5-Year Extended Warranty - For PDUMH15AT and PDUMH20AT only	1
Power Cables	<a href="#">P002-002</a>	2-ft. Power Cord (IEC-320-C14 to NEMA 5-15R)	1
Power Cables	<a href="#">P005-002</a>	2-ft. Heavy-Duty 14AWG Power cord ( IEC-320-C13 to IEC-320-C14)	1
Power Cables	<a href="#">P005-006</a>	6-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to IEC-320-C14)	1
Power Cables	<a href="#">P005-010</a>	10-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to IEC-320-C14)	1
Power Cables	<a href="#">P007-002</a>	2-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to NEMA 5-15P)	1
Power Cables	<a href="#">P007-006</a>	6-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to NEMA 5-15P)	1
Power Cables	<a href="#">P007-010</a>	10-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to NEMA 5-15P)	1
Power Cables	<a href="#">P010-012</a>	12-ft. 18AWG Power cord (NEMA 5-15P to IEC-320-C13)	1

Power Cables	<a href="#">P012-006</a>	6-ft. Notebook Power cord (NEMA 1-15P to IEC-320-C7)	1
Power Cables	<a href="#">P022-001</a>	1-ft. 18AWG Power Extension cord (NEMA 5-15R to NEMA 5-15P)	1
Power Cables	<a href="#">P023-001</a>	1-ft. 14AWG Power Adapter cord (NEMA L5-15R to NEMA 5-15P)	1
Power Cables	<a href="#">P032-007</a>	7-ft. 12AWG Heavy Duty Power cord ( IEC-320- C13 to IEC-320-C20	1
Power Cables	<a href="#">P034-010</a>	10-ft. 14AWG Heavy Duty Power cord ( IEC-320-C19 to NEMA 5-15P)	1
Rack Accessories	<a href="#">SRSWITCH</a>	Magnetic Door Switch Kit (2-pack for front and rear doors; requires ENVIROSENSE.)	1
SNMP Accessories	<a href="#">ENVIROSENSE</a>	Monitors temperature, humidity and contact-closure inputs. (Requires SNMPWEBCARD or switched PDU.)	1
SNMP Accessories	<a href="#">SNMPWEBCARD</a>	For remote monitoring and control via SNMP, Web, or Telnet.	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=3456](http://www.tripplite.com/en/products/model.cfm?txtModelID=3456).

Copyright © 2011 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.