



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: PDUMH20

**Single-Phase Metered PDU, 20A 120V, 1U Horizontal Rackmount, NEMA 5-15/20R outlets, NEMA L5-20P input with 5-20P adapter**

### Highlights

- Metered single phase 20A 120V PDU
- 1U horizontal rackmount; digital current meter
- NEMA 5-20P / L5-20P input; 15 ft. / 4.5m line cord
- 12 NEMA 5-15/20R outlets
- Reversible housing; 4.5 in. / 11.4 cm depth



### Description

Tripp Lite Metered PDU / Power Distribution Units offer real-time local reporting of load level in amps via built-in digital meter. Enables visual current monitoring of PDU output current to prevent circuit overloads as additional equipment is added. Offers reliable rackmount multi-outlet power distribution from any protected UPS, generator or mains input power source. High quality design includes rugged all-metal housing and secure rackmount installation with included mounting accessories.

#### Applications

- Multi-outlet power distribution unit with digital current monitoring is the ideal means of powering multiple loads in 19 inch rackmount, wall-mount, and under-counter applications such as internetworking, PC systems, telecommunications, audio visual, security, sound reinforcement, and more. Ideal distribution of alternate and sinewave UPS and generator power or commercially derived AC power to connected equipment.

#### Package Includes

- PDUMH20 Metered rackmount PDU
- L5-20R to 5-20P plug adapter
- Owner's manual with warranty information

### Features

- 20A single phase 120V Metered Power Distribution Unit / PDU
- Built-in 2 digit visual meter continuously reports PDU load level in amps
- Attached NEMA L5-20P 20A 120V input plug with 15 ft. / 4.5m line cord
- Includes 5-20P 20A 120V plug adapter
- 1U horizontal rackmount format installs in one rack space
- 12 NEMA 5-15/20R outlets
- Mounting flanges support installation in 2 and 4 post racks, with additional support for wall-mount and under-counter installation formats
- Optional PDUSIDEBRKT enables 0U vertical rackmount in compatible racks
- Back panel grounding lug
- Lifetime limited warranty

### Specifications

#### OVERVIEW

Model Type	Metered
PDU Type	Metered
<b>OUTPUT</b>	
Frequency compatibility	50 / 60 Hz
Output nominal voltage	120V
Overload protection	20A
Outlet quantity / type	12 NEMA 5-15/20R
<b>INPUT</b>	
PDU Input Voltage	100; 120; 127
Recommended Electrical Service	120V
Maximum Input Amps (A)	20
Input connection type	NEMA L5-20P with NEMA 5-20P plug adapter
Plug Type	NEMA L5-20P (20A 120V)
PDU Plug Type	NEMA 5-20P; NEMA L5-20P
Input cord length (ft.)	15
Voltage compatibility (VAC)	120
Phase	Single-Phase
<b>LEDS ALARMS &amp; SWITCHES</b>	
Front panel LEDs	Digital LED current meter
<b>PHYSICAL</b>	
Shipping weight (lbs)	3.6
Shipping weight (kg)	1.6
Unit Dimensions (HWD/in)	1.75 (1U) x 17.5 x 4.5
Unit Dimensions (HWD/cm)	4.45 x 44.5 x 11.4
Shipping Dimensions (HWD/in)	2.25 x 20.5 x 10
Shipping Dimensions (HWD/cm)	5.7 x 52.1 x 25.4
Unit weight (lbs)	3
Unit weight (kg)	1.4
Material of construction	Sheet Metal
Style	Rackmount, Vertical Rackmount, Wallmount/Under-Counter
Form factors supported	1U rackmount, 0U vertical rackmount, wall-mount, and under-counter installation
PDU Form Factor	Horizontal (1U, 2U, etc)
<b>SPECIAL FEATURES</b>	
Appearance	All black color scheme

<b>TVSS grounding</b>	Rear grounding lug
<b>CERTIFICATIONS</b>	
<b>Certifications</b>	Tested to UL60950-1 (USA) and CAN/CSA C22.2 No. 60950-1-03 (Canada), RoHS Compliant
<b>WARRANTY</b>	
<b>Product Warranty Period (U.S., Canada &amp; Puerto Rico)</b>	Lifetime limited warranty

## Related Items

### Optional Products

Product Type	Related Model	Description	Qty.
Power Cables	<a href="#">P007-002</a>	2-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to NEMA 5-15P)	1
Power Cables	<a href="#">P007-006</a>	6-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to NEMA 5-15P)	1
Power Cables	<a href="#">P007-010</a>	10-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to NEMA 5-15P)	1
Power Cables	<a href="#">P010-012</a>	12-ft. 18AWG Power cord (NEMA 5-15P to IEC-320-C13)	1
Power Cables	<a href="#">P012-006</a>	6-ft. Notebook Power cord (NEMA 1-15P to IEC-320-C7)	1
Power Cables	<a href="#">P022-001</a>	1-ft. 18AWG Power Extension cord (NEMA 5-15R to NEMA 5-15P)	1
Power Cables	<a href="#">P023-001</a>	1-ft. 14AWG Power Adapter cord (NEMA L5-15R to NEMA 5-15P)	1
Power Cables	<a href="#">P034-010</a>	10-ft. 14AWG Heavy Duty Power cord (IEC-320-C19 to NEMA 5-15P)	1
Power Cables	<a href="#">P043-002</a>	2-ft. 10AWG Heavy Duty Power Cord with 20 AMP Breaker, (NEMA L5-30P to NEMA L5-20R)	1
Power Cables	<a href="#">P049-010</a>	10-ft. 12AWG Heavy Duty Power cord (IEC-320-C19 to NEMA 5-20P)	1
Rackmount/Wallmount Kits	<a href="#">PDUSIDEBRKT</a>	Enables Vertical Installation of Select 1U PDUs, Power Strips and Surge Suppressors in SmartRack Configurations	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=3867](http://www.tripplite.com/en/products/model.cfm?txtModelID=3867).

Copyright © 2011 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.