

Model #: PDUV20

Single-Phase Basic PDU, 20A 120V, 0U Vertical Rackmount, NEMA 5-15/20R outlets, NEMA 5-20P input plug



Highlights

- 12 outlets
- · Integrated button mounts
- 20-amp breaker
- 15-ft. cord
- 36" length

Description

Tripp Lite's PDUV20 Basic Vertical Power Distribution Unit offers 20-amp, 120V multi-outlet AC power distribution in a convenient 36-inch mountable housing. It offers vertical power distribution in rackmount, raceway and workbench applications. Includes 12 NEMA 5-15/20R output receptacles and 15-ft. AC line cord. Sturdy all-metal aluminum housing stands up to demanding network, laboratory or factory environments. Unfiltered electrical pass-through makes the PDUV20 ideal for distributing alternate waveform UPS or generator power in rack enclosures, network closets and more. Included 12 NEMA5-15/20R outlets, 15-ft. AC power cord with 5-20P plug, 20-amp circuit breaker in rugged metal case design with universal and button mounting options. PLUG/OUTLETS - Input: NEMA 5-20P/Output: 12 NEMA 5-15/20R ELECTRICAL - 120V AC, 50/60Hz, 20A FORMAT - 36-inch mountable strip format

Applications

• Ideal for horizontal or vertical raceway-style power distribution in office, workbench, industrial, networking and telecom applications.

Package Includes

- PDUV20 Basic Vertical PDU
- Mounting hardware
- Owner's manual with warranty information

Features

- Sturdy all-metal, 36-inch corded PDU
- Includes integrated button mount and hardware for 0U configuration in rack enclosures as well as horizontal mounting in raceways and more
- 12 NEMA 5-15/20R output receptacles
- 20-amp electrical capacity with circuit breaker
- 120V, 50/60Hz electrical compatibility
- 15-ft. power cord
- Lifetime warranty

Specifications

OVERVIEW

Model Type	Basic		
PDU Type	Basic		
OUTPUT			
Frequency compatibility	50 / 60 Hz		
Output VA	2400		
Output nominal voltage	120V		
Overload protection	20A		
Outlet quantity / type	12 NEMA 5-15/20R		
INPUT			
PDU Input Voltage	100; 120; 127		
Recommended Electrical Service	120V		
Maximum Input Amps (A)	20		
Input connection type	NEMA 5-20P		
Plug Type	NEMA 5-20P (20A 120V)		
PDU Plug Type	NEMA 5-20P		
Input cord length (ft.)	15		
Voltage compatibility (VAC)	120		
Phase	Single-Phase		
PHYSICAL			
Shipping weight (lbs)	3.8		
Unit Dimensions (HWD/in)	1.75 x 36 x 1.25		
Shipping Dimensions (HWD/in)	3 x 40 x 2.75		
Unit weight (lbs)	3.3		
Material of construction	Aluminum		
Style	Vertical Rackmount, Wallmount, Raceway, Workbench		
Form factors supported	Vertical (0U) mounting in rack enclosures, horizontal mount in raceways and a variety of other applications		
PDU Form Factor	Vertical (0U)		
SPECIAL FEATURES			
Appearance	Black housing		
CERTIFICATIONS			
Certifications	Tested to UL60950-1 (USA) and CAN/CSA C22.2 No. 60950-1-03 (Canada), RoHS Compliant		
WARRANTY			
Product Warranty Period (U.S., Canada & Puerto Rico)	Lifetime limited warranty		

Related Items

Optional Products

Product Type	Related Model	Description	Qty.
Power Cables	P007-002	2-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to NEMA 5-15P)	1
Power Cables	P007-006	6-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to NEMA 5-15P)	1
Power Cables	P007-010	10-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to NEMA 5-15P)	1
Power Cables	P010-012	12-ft. 18AWG Power cord (NEMA 5-15P to IEC-320-C13)	1
Power Cables	P012-006	6-ft. Notebook Power cord (NEMA 1-15P to IEC-320-C7)	1
Power Cables	P022-001	1-ft. 18AWG Power Extension cord (NEMA 5-15R to NEMA 5-15P)	1
Power Cables	P023-001	1-ft. 14AWG Power Adapter cord (NEMA L5-15R to NEMA 5-15P)	1
Power Cables	P034-010	10-ft. 14AWG Heavy Duty Power cord (IEC-320-C19 to NEMA 5-15P)	1
Power Cables	P044-06I	6-inch 12AWG Heavy Duty Power Adapter cord (NEMA-L5-20R to NEMA-5-20P)	1
Power Cables	P049-010	10-ft. 12AWG Heavy Duty Power cord (IEC-320-C19 to NEMA 5-20P)	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=3881.

Copyright © 2011 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.