



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: SUPDMB568HW

SUPDMB568HW - UPS Accessory - Hardwire PDU Module

Highlights

- Converts compatible SmartOnline Hot-Swappable Modular UPS systems to hardwire input and output
- For use with input voltages of 120/208 or 120/240 VAC split-phase power
- Convenient quick-disconnect terminal block allows installation in minutes
- Manual bypass switch eliminates equipment downtime



Description

The SUPDMB568HW hardwire input/output PDU module converts compatible SmartOnline Hot-Swappable Modular UPS Systems (models SU5000RT4U, SU6000RT4U, and SU8000RT4U) to a totally hardwired solution. Easy quick-connect terminal block allows installation of hardwire distribution module in minutes. Can accept input voltages of 120/208 or 120/240 VAC split-phase power. Detachable hardwire module with manual bypass switch allows for effortless UPS maintenance without the need to power down connected loads and re-wire input/output connections.

Applications

- Use with Tripp Lite SU5000RT4U, SU6000RT4U, and SU8000RT4U UPS systems in 120, 208/240V applications where hardwire input/output connections are required

System Requirements

- Use with SU5000RT4U, SU6000RT4U, and SU8000RT4U split-phase SmartOnline Hot-Swappable Modular UPS Systems

Package Includes

- SUPDMB568HW hardwire PDU
- Mounting Hardware
- Owner's Manual

Specifications

OVERVIEW	
Model Type	PDU Modules
OUTPUT	
Frequency compatibility	50 / 60 Hz
Output nominal voltage	120/208, 120/240
Outlet quantity / type	Split-phase hardwire (4-wire)
INPUT	
Input connection type	Split-phase hardwire (4-wire)

Voltage compatibility (VAC)	100-140
PHYSICAL	
Shipping weight (lbs)	14
Shipping weight (kg)	6.3
Unit Dimensions (HWD/in)	6 x 17.5 x 6.75
Unit Dimensions (HWD/cm)	15.24 x 44.45 x 17.1
Shipping Dimensions (HWD/in)	9.5 x 20.5 x 9.75
Shipping Dimensions (HWD/cm)	24.1 x 52.1 x 24.8
Unit weight (lbs)	11.7
Unit weight (kg)	5.3
Material of construction	Steel
SPECIAL FEATURES	
Appearance	All-black color scheme
CERTIFICATIONS	
Certifications	Tested to UL1778 (USA), CSA (Canada), RoHS compliant
WARRANTY	
Product Warranty Period (U.S., Canada & Puerto Rico)	2-year limited warranty

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=4188.

Copyright © 2011 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.