

Model #: SRW10US

SmartRack 10U Wall Mount Rack Enclosure Cabinet



Highlights

- 10U with adjustable front and rear vertical rackmount rails
- Hinged cabinet swings away from wall bracket for easy equipment access (swing direction is reversible)
- Locking, reversible front door and locking, removable side panels
- Fully assembled for quick installation

Description

The SRW10US 10U Wall Mount Rack Enclosure Cabinet is designed to integrate wall-mounting, easy equipment access, and cable management in IT network applications with limited floor space. Ventilated front door and side panels allow generous airflow to keep equipment operating safely. Adjustable rack rails with square mounting holes accommodate up to 10U of standard 19" rackmount equipment. Supports up to 140 lbs of equipment. A sturdy hinge between the cabinet and the wall-mount bracket allows the cabinet to swing away from the wall for easy access to equipment and cabling. Top and bottom panels include convenient cutouts for cable routing.

Features

- 10U wall-mounted enclosure
- Adjustable mounting depths from 3" to 20.5" inches
- Ventilated front door and side panels for increased airflow
- Hinged cabinet swings away from wall bracket for easy equipment and cable access
- Locking, reversible front door
- Locking, removable side panels
- Top and bottom panel cable access openings
- Fully assembled for quick installation
- 5 year warranty

Specifications

PHYSICAL	
Installed whole system maximum rack depth (inches)	20.5
Installed whole system minimum rack depth (inches)	3
Installed whole system total rack space height (rack spaces)	10U

Shipping weight (lbs)	59	
Shipping weight (kg)	26.76	
Shipping Dimensions (HWD/in)	24.41 x 26.38 x 24.41	
Shipping Dimensions (HWD/cm)	62 x 67 x 62	
Unit weight (lbs)	55	
Unit weight (kg)	24.94	
Unit Dimensions (cm)	EXTERNAL DIMENSIONS: 54.78 x 60 x 54.9 (HWD)	
Unit Dimensions (in)	EXERNAL DIMENSIONS: 21.57 x 23.62 x 21.5 (HWD)	
Color	Black	
Weight Capacity - Stationary (lbs)	200	
SPECIAL FEATURES		
Grounding lug	Front and Back door frames	
CERTIFICATIONS		
NOM (Mexico)	Tested to NOM (Mexico)	
Approvals	EIA-310-E, IEC 60297-3-100, RoHS, DIN 41494, IP20 Protection Rating, UL 60950	
WARRANTY		
Product Warranty Period (U.S., Canada & Puerto Rico)	5-year limited warranty	

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=4743.

Copyright © 2011 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.