

# Model #: SR12UB

#### **SmartRack 12U Extra Depth Rack Enclosure Cabinet**



#### **Highlights**

- 12U with adjustable front and rear vertical rackmount rails
- Extended depth of 33" allow for standard server installation
- Locking, reversible front door and locking, removable side panels
- Fully assembled for quick installation
- · Casters and leveling feet

### **Description**

SmartRack enclosures are designed for secure, high density server and networking applications in IT environments. Designed with provisions to integrate cooling, power distribution and cable management, SmartRack enclosures make ideal homes for mission-critical equipment. Ventilated front door and side panels allow generous airflow to keep equipment operating safely. Adjustable rack rails with square mounting holes accommodate up to 12U of standard 19" rackmount equipment. Supports up to 300lbs of equipment. Top and bottom panels include convenient cutouts for cable routing.

#### **Features**

- 12U extra deep enclosure
- Adjustable mounting depths from 3" to 32.5" inches
- Locking, reversible front door
- Locking, removable side panels
- Top and bottom panel cable access openings
- Fully assembled for quick installation
- Casters and leveling feet
- 5 year warranty

## **Specifications**

| PHYSICAL   |      |
|--|------|
| Installed whole system maximum rack depth (inches)           | 32.5 |
| Installed whole system minimum rack depth (inches)           | 3    |
| Installed whole system total rack space height (rack spaces) | 12U  |
| Shipping weight (lbs)  | 123  |
| Shipping weight (kg)   | 55.8 |

| Shipping Dimensions<br>(HWD/in)                         | 37.8 x 26.9 x 25.6                           |  |
|---|--|--|
| Shipping Dimensions<br>(HWD/cm)                         | 96 x 68.32 x 65                              |  |
| Unit weight (lbs)                                       | 105  |  |
| Unit weight (kg)  | 48   |  |
| Unit Dimensions (cm)                                    | EXTERNAL DIMENSIONS: 63.5 x 60 x 85.09 (HWD) |  |
| Unit Dimensions (in)                                    | EXTERNAL DIMENSIONS: 25 x 23.63 x 33.5 (HWD) |  |
| Color   | Black  |  |
| Weight Capacity - Stationary (lbs)                      | 250  |  |
| Units per Pallet  | 1  |  |
| SPECIAL FEATURES  |  |  |
| Grounding lug   | Front and Back door frames                   |  |
| CERTIFICATIONS  |  |  |
| Certifications  | EIA-310-E                                    |  |
| NOM (Mexico)  | Tested to NOM (Mexico)                       |  |
| Approvals   | UL60950; RoHS                                |  |
| WARRANTY  |  |  |
| Product Warranty Period<br>(U.S., Canada & Puerto Rico) | 5-year limited warranty                      |  |

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=4733.

Copyright © 2011 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.