

# Model #: PDUH20HVL6

Single-Phase Basic PDU, 20A 208/240V, 1U Horizontal Rackmount, C19 & C13 outlets, NEMA L6-20P input plug



# **Highlights**

- Basic single phase 20A 208/240V PDU
- 1U horizontal rackmount installation
- L6-20P input; 15 ft. / 4.5m line cord
- 2 C19 and 12 C13 outlets
- Reversible housing; 3.75 in. / 9.5cm depth

### **Description**

Tripp Lite Basic Power Distribution Units / PDU systems offer reliable rackmount power distribution. Supplies equipment with continuous power from any protected UPS, generator or mains input power source. High quality design includes rugged all-metal housing and secure rackmount installation with included mounting accessories.

# Applications

• Ideal for datacenters, network closets, equipment racks and a wide variety of other application types

#### Package Includes

- PDUH20HVL6 PDU rackmount PDU
- Owner's manual

### **Features**

- 20A single phase 208/240V Basic Power Distribution Unit / PDU
- Attached NEMA L6-20P input
- 14 outlets (2 C19, 12 C13)
- 15 ft. / 4.5m line cord
- 1U horizontal rackmount format installs in one rack space
- Mounting flanges support installation in 2 and 4 post racks, with additional support for wall-mount and under-counter installation formats
- Reversible housing
- Back panel grounding lug

### **Specifications**

OVERVIEW	
Model Type	Basic
PDU Type	Basic
OUTPUT	
Frequency compatibility	50 / 60 Hz

Output nominal voltage	208/240V		
Overload protection	n/a		
Outlet quantity / type	2 C19, 12 C13		
INPUT			
PDU Input Voltage	208; 240		
Recommended Electrical Service	208/240V 20A		
Maximum Input Amps (A)	20		
Input connection type	L6-20P		
Plug Type	NEMA L6-20P (20A, 208/240V)		
PDU Plug Type	NEMA L6-20P		
Input cord length (ft.)	15		
Input cord length (m)	4.5		
Input cord details	Input cable is attached		
Voltage compatibility (VAC)	208/240		
Phase	Single-Phase		
PHYSICAL			
Shipping weight (lbs)	5.9		
Shipping weight (kg)	2.7		
Unit Dimensions (HWD/in)	1.75 (1U) x 17.25 x 3.75		
Unit Dimensions (HWD/cm)	4.45 x 43.8 x 9.5		
Shipping Dimensions (HWD/in)	2.25 x 20.5 x 9.5		
Shipping Dimensions (HWD/cm)	5.7 x 52.1 x 24.1		
Unit weight (lbs)	3.75		
Unit weight (kg)	1.7		
Material of construction	Sheet Metal		
Style	Rackmount, Vertical Rackmount, Wallmount/Under-Counter		
Form factors supported	1U rackmount, 0U vertical rackmount, wall-mount, and under-counter installation		
PDU Form Factor	Horizontal (1U, 2U, etc)		
SPECIAL FEATURES			
Appearance	All black color scheme		
TVSS grounding	Rear grounding lug		
CERTIFICATIONS			
Certifications	Tested to UL 60950 (USA), CSA (Canada), RoHS Compliant		
WARRANTY			

# **Related Items**

# **Optional Products**

Product Type	Related Model	Description	Qty.
Power Cables	P005-002	2-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to IEC-320-C14)	1
Power Cables	P005-006	6-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to IEC-320-C14)	1
Power Cables	P005-010	10-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to IEC-320-C14)	1
Power Cables	P032-007	7-ft. 12AWG Heavy Duty Power cord ( IEC-320- C13 to IEC-320-C20	1
Power Cables	P036-002	2-ft. 12AWG Heavy Duty Power cord (IEC-320-C19 to IEC-320-C20)	1
Power Cables	P036-006	6-ft. 12AWG Heavy Duty Power cord (IEC-320-C19 to IEC-320-C20)	1
Power Cables	P047-002	2-ft. 14AWG Heavy Duty Power cord (IEC-320-C19 to IEC-320-C14)	1
Power Cables	P047-004	4-ft. 14AWG Heavy Duty Power cord (IEC-320-C19 to IEC-320-C14)	1
Power Cables	P047-006	6-ft. 14AWG Heavy Duty Power cord (IEC-320-C19 to IEC-320-C14)	1
Power Cables	P047-010	10-ft. 14AWG Heavy Duty Power cord (IEC-320-C19 to IEC-320-C14)	1
Rack Accessories	PDUSIDEBRKT	Enables Vertical Installation of Select 1U PDUs, Power Strips and Surge Suppressors in SmartRack Configurations	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=4807.

Copyright © 2011 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.