



**Tripp Lite**  
 1111 West 35th Street  
 Chicago, IL 60609 USA  
 Telephone: +(773) 869 1234  
 E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: PDUH20DV

**Single-Phase Basic PDU, 20A 100-240V, 1U Horizontal Rackmount, C19 & C13 outlets, C20 inlet, C20 line cord and L6-20P adapter**

### Highlights

- Basic single phase 20A 100-240V PDU
- 1U horizontal rackmount installation
- C20 input with NEMA L6-20P adapter; 12 ft. / 3.7m line cord
- 2 C19 and 12 C13 outlets
- Reversible housing; 3.75 in. / 9.5cm depth



### Description

Tripp Lite Basic Power Distribution Units / PDU systems offer reliable rackmount power distribution. Supplies equipment with continuous power from any protected UPS, generator or mains input power source. High quality design includes rugged all-metal housing and secure rackmount installation with included mounting accessories.

#### Applications

- Ideal for datacenters, network closets, equipment racks and a wide variety of other application types

#### Package Includes

- PDUH20DV PDU rackmount PDU
- Owner's manual

### Features

- 20A single phase 100-240V Basic Power Distribution Unit / PDU
- C20 inlet with included C19 to C20 input cable and L6-20P adapter
- 14 outlets (2 C19, 12 C13)
- 12 ft. / 3.7m line cord
- 1U horizontal rackmount format installs in one rack space
- Mounting flanges support installation in 2 and 4 post racks, with additional support for wall-mount and under-counter installation formats
- Reversible housing
- Back panel grounding lug

### Specifications

| OVERVIEW                |            |
|-------------------------|------------|
| Model Type              | Basic      |
| PDU Type                | Basic      |
| OUTPUT                  |            |
| Frequency compatibility | 50 / 60 Hz |

|  |   |
|--|---|
| Output nominal voltage                               | 100-240V  |
| Overload protection                                  | n/a   |
| Outlet quantity / type                               | 2 C19, 12 C13   |
| <b>INPUT</b>   |   |
| PDU Input Voltage                                    | 100; 120; 127; 200; 208; 230; 240   |
| Maximum Input Amps (A)                               | 20  |
| PDU Plug Type  | NEMA L6-20P; IEC-320 C20  |
| Input cord length (ft.)                              | 12  |
| Input cord length (m)                                | 3.7   |
| Input cord details                                   | Input cable is detachable PDU C20 inlet   |
| Voltage compatibility (VAC)                          | 100; 120; 127; 200; 208; 230; 240   |
| Phase  | Single-Phase  |
| <b>PHYSICAL</b>                                      |   |
| Shipping weight (lbs)                                | 5.7   |
| Shipping weight (kg)                                 | 2.6   |
| Unit Dimensions (HWD/in)                             | 1.75 (1U) x 17.25 x 3.75  |
| Unit Dimensions (HWD/cm)                             | 4.45 x 43.8 x 9.5   |
| Shipping Dimensions (HWD/in)                         | 2.25 x 20.5 x 9.5   |
| Shipping Dimensions (HWD/cm)                         | 5.7 x 52.1 x 24.1   |
| Unit weight (lbs)                                    | 3.75  |
| Unit weight (kg)                                     | 1.7   |
| Material of construction                             | Sheet metal   |
| Style  | Rackmount, Vertical Rackmount, Wallmount/Under-Counter                          |
| Form factors supported                               | 1U rackmount, 0U vertical rackmount, wall-mount, and under-counter installation |
| PDU Form Factor                                      | Horizontal (1U, 2U, etc)  |
| <b>SPECIAL FEATURES</b>                              |   |
| Appearance   | All black color scheme  |
| TVSS grounding                                       | Rear grounding lug  |
| <b>CERTIFICATIONS</b>                                |   |
| Certifications                                       | Tested to UL 60950 (USA), CSA (Canada), CE (EU), RoHS Compliant                 |
| <b>WARRANTY</b>                                      |   |
| Product Warranty Period (U.S., Canada & Puerto Rico) | Lifetime limited warranty   |

## Related Items

### Optional Products

| Product Type     | Related Model               | Description   | Qty. |
|------------------|-----------------------------|---|------|
| Power Cables     | <a href="#">P002-002</a>    | 2-ft. Power Cord<br>(IEC-320-C14 to NEMA 5-15R)   | 1    |
| Power Cables     | <a href="#">P005-002</a>    | 2-ft. Heavy-Duty 14AWG Power cord<br>( IEC-320-C13 to IEC-320-C14)  | 1    |
| Power Cables     | <a href="#">P005-006</a>    | 6-ft. Heavy-Duty 14AWG Power cord<br>(IEC-320-C13 to IEC-320-C14)   | 1    |
| Power Cables     | <a href="#">P005-010</a>    | 10-ft. Heavy-Duty 14AWG Power cord<br>(IEC-320-C13 to IEC-320-C14)  | 1    |
| Power Cables     | <a href="#">P032-007</a>    | 7-ft. 12AWG Heavy Duty Power cord<br>( IEC-320- C13 to IEC-320-C20)   | 1    |
| Power Cables     | <a href="#">P034-010</a>    | 10-ft. 14AWG Heavy Duty Power cord<br>( IEC-320-C19 to NEMA 5-15P)  | 1    |
| Power Cables     | <a href="#">P036-002</a>    | 2-ft. 12AWG Heavy Duty Power cord<br>(IEC-320-C19 to IEC-320-C20)   | 1    |
| Power Cables     | <a href="#">P036-006</a>    | 6-ft. 12AWG Heavy Duty Power cord<br>(IEC-320-C19 to IEC-320-C20)   | 1    |
| Power Cables     | <a href="#">P040-010</a>    | 10-ft. 12AWG Heavy Duty Power cord<br>(IEC-320-C19 to IEC-320-L6-20P)   | 1    |
| Power Cables     | <a href="#">P045-010</a>    | 10-ft. 12AWG Heavy-Duty Power cord<br>(IEC-320-C19 to NEMA L5-20P)  | 1    |
| Power Cables     | <a href="#">P047-002</a>    | 2-ft. 14AWG Heavy Duty Power cord<br>(IEC-320-C19 to IEC-320-C14)   | 1    |
| Power Cables     | <a href="#">P047-004</a>    | 4-ft. 14AWG Heavy Duty Power cord<br>(IEC-320-C19 to IEC-320-C14)   | 1    |
| Power Cables     | <a href="#">P047-006</a>    | 6-ft. 14AWG Heavy Duty Power cord<br>(IEC-320-C19 to IEC-320-C14)   | 1    |
| Power Cables     | <a href="#">P047-010</a>    | 10-ft. 14AWG Heavy Duty Power cord<br>(IEC-320-C19 to IEC-320-C14)  | 1    |
| Power Cables     | <a href="#">P049-010</a>    | 10-ft. 12AWG Heavy Duty Power cord<br>(IEC-320-C19 to NEMA 5-20P)   | 1    |
| Power Cables     | <a href="#">P050-008</a>    | 8-ft. Power cord<br>(IEC-320-C19 to CEE 7/7 SCHUKO)   | 1    |
| Power Cables     | <a href="#">P052-008</a>    | 8-ft. Power cord<br>(IEC-320-C19 to BS1363 UK Plug)   | 1    |
| Power Cables     | <a href="#">P070-010</a>    | 10-ft. IEC309 to C19 Power Cord   | 1    |
| Rack Accessories | <a href="#">PDUSIDEBRKT</a> | Enables Vertical Installation of Select 1U PDUs, Power Strips and Surge Suppressors in SmartRack Configurations | 1    |

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=4799](http://www.tripplite.com/en/products/model.cfm?txtModelID=4799).

Copyright © 2011 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.