

Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

# Model #: STRIKER

## 7 oultet, 6-ft cord, 1080 joule strip - Protect It! Surge Suppressor



## **Highlights**

- 7 outlets/6-ft. cord
- 1080 joule surge suppression rating
- \$20,000 Ultimate Lifetime Insurance (USA & Canada only)

### **Description**

Tripp Lite's STRIKER offers economical AC surge suppression for protection of workstations, desktop PCs, telecom systems and other sensitive electronics. AC surge suppression shields connected equipment from damage and performance problems due to transient surges. STRIKER offers 7 AC outlets, 6-ft. cord and diagnostic LEDs to warn of wiring problems and suppressor damage. AC suppression rated at 1080 joules shields equipment from surges and line noise. Attractive gray housing with keyhole mounting tabs and 1 designated transformer plug outlet offer convenient protection of desktop computer equipment and accessories. \$20,000 Ultimate Lifetime Insurance (USA & Canada only).

PLUG/OUTLETS: Input: NEMA5-15P/Output: 7 x NEMA5-15R/6-ft. AC line cord

ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires NEMA5-15R wall receptacle)

FORMAT: Corded multi-outlet strip with 1 transformer-spaced outlet

SUPPRESSION: AC: 150V RMS Clamping/1080 joules/400V UL1449 Let-through Rating

#### Applications

• Ideal for any desktop, network or home computing application requiring AC line surge protection.

#### Package Includes

- STRIKER Surge Suppressor
- Instruction manual with warranty information

### **Features**

- 7 outlets
- 6-ft. cord
- Surge suppression rating: 1080 joules
- EMI/RFI noise filtering
- Can accommodate 1 transformer without blocking remaining outlets
- Diagnostic LEDs indicate protection present & ground present
- . Keyhole supports for wall mounting
- · Lifetime product warranty

# **Specifications**

OVERVIEW		
Intended Application	Home/Office	
ОИТРИТ		
Frequency compatibility	50 / 60 Hz	
Output watts	1800	
Circuit Breaker (amps)	15	
Outlet quantity / type	7 NEMA 5-15R	
Transformer accommodation	Supports 1 large transformer plug accessory without covering remaining outlets; accepts up to 4 transformers total	
Outlet orientation	Single row	
INPUT		
Recommended Electrical Service	120V (110-125V)	
Input connection type	NEMA 5-15P	
Input cord length (ft.)	6	
Input cord gauge, type	14 gauge, SJT	
Voltage compatibility (VAC)	120	
LEDS ALARMS & SWITCHES		
Switches	Combination AC circuit breaker and 2-position red illuminated on/off power switch	
Diagnostic LEDs	Built-in LED confirms suppressor "protection present" (green) status	
SURGE / NOISE SUPPRESSION		
AC suppression joule rating	1080	
AC suppression response time	< 1 ns	
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression	
Clamping voltage (RMS)	150	
UL1499 let through rating	400V	
EMI / RFI filtering	Up to 20 dB	
DATALINE SURGE SUPPRESSION		
Cable (Coax) Protection	No	
Network (Ethernet) Protection	No	
PHYSICAL		
Shipping weight (lbs)	1.30	
Unit Dimensions (HWD/in)	1.32 x 2.05 x 11.69	

Shipping Dimensions (HWD/in)	13.78 x 4.52 x 1.77	
Unit weight (lbs)	1.17	
Material of construction	Plastic	
Integrated keyhole mounting tabs	Keyhole mounting tabs enable wall mounting	
AC line cord color	Gray	
Style	Strip	
CERTIFICATIONS		
UL1449 3rd Edition (AC Suppression)	UL1449 3rd Edition	
NOM (Mexico)	NOM	
UL1363 (Power Tap)	UL1363	
cUL / CSA (Canada)	cUL	
Approvals	Exceeds IEEE 587 category A&B specifications	
WARRANTY		
Product Warranty Period (U.S., Canada & Puerto Rico)	Lifetime limited warranty	
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$20,000 Ultimate Lifetime Insurance	

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=133.

Copyright © 2011 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.