




Model No.	Form Factor	Dimension (inches)			Assembly Required?	Loading Capacity (lbs)	Door	Internal Depth	Removable Side panels	Security	Casters	Page No.
		W	H	D								
WO15AB	15U	22.13	34.60	39.60	Yes	330	No	Outside Post-to-post [Depth]: Max:31.5" / Min:9.5"; Inside Post-to-post [Depth]: Max:23.5" / Min:2.0"; Hole-to-hole [Depth]: Max:27.35" / Min:5.5";	No	-	Yes	42
WO22AB	22U	22.13	46.25	39.60	Yes	330	No	Outside Post-to-post [Depth]: Max:31.5" / Min:9.5"; Inside Post-to-post [Depth]: Max:23.5" / Min:2.0"; Hole-to-hole [Depth]: Max:27.35" / Min:5.5";	No	-	Yes	43
WO36AB	36U	22.13	70.50	39.60	Yes	330	No	Outside Post-to-post [Depth]: Max:31.5" / Min:9.5"; Inside Post-to-post [Depth]: Max:23.5" / Min:2.0"; Hole-to-hole [Depth]: Max:27.35" / Min:5.5";	No	-	Yes	43
WO45AB	45U	22.13	86.50	39.60	Yes	330	No	Outside Post-to-post [Depth]: Max:31.5" / Min:9.5"; Inside Post-to-post [Depth]: Max:23.5" / Min:2.0"; Hole-to-hole [Depth]: Max:27.35" / Min:5.5";	No	-	Yes	43

WO15AB

15U 4 Post Open Frame Rack



Features

- Open Frame Construction Enables Quick Access to Rackmount System
- Max Air Flow and Temperature Control by Central AC or by Room
- Easy to Transport with Rolling Caster
- Manufactured in Accordance with ANSI / EIA RS-310-D, IEC297-2, DIN41491 (PART 1), DIN41494 (PART7) and GB / T3047.2-921 Standards
- Modular Design, Easily Assemble and Disassemble For Logistic and Relocation of Cabinet to Enable Cost-Effective Solution



Introduction

Claytek open frame rack provide simplicity with mobility. Quick and easy assembly steps to setup open rack. The WO sturdy steel frame construction enforces stability and durability. Steel iron castors come standard to help moving the server easily to any location. Open frame rack has higher thermal manageability by room or central air conditioning. The WO series is a flexible and cost-effective solution for rackmount cabinet.

Shipping Information

Shipper Design	Standard Carton
Shipper Dimension (inch)	27x13x42
Weight	55.13 lbs
Pallet Load	4

Specifications

Color	Black
Industry Standard	ANSI/EIA RS-310D, DIN41491, PART1, IEC297-2, PART7, GB/T3047.2-92
Internal Dimensions	Outside Post-to-post [Depth]: Max:31.5" / Min:9.5";
	Inside Post-to-post [Depth]: Max:23.5" / Min:2.0";
	Hole-to-hole [Depth]: Max:27.35" / Min:5.5";
Surface Treatment	Degreasing, Phosphoric, and Powder Coat
Packaging Dimensions (W x H x D)	25.98 x 33.07 x 11.22 inch

Accessories

WA-CM1UB	1U Cable Management Rack Kit
WA-CM2UB	2U Cable Management Rack Kit
WA-KBR96B	1U Compact Sliding Keyboard Drawer
WA-LB96B	Cabinet Supporting Bar
WA-PD010	10 Outlet Overload Circuit Breaker Protection Power Distribution Unit
WA-PD014	14 Outlet Lightning Surge Protection Power Distribution Unit
WA-PS06A	6 Outlet Power Strip
WA-SF96B	Heavy Duty Rackmount Shelf
WA-SFR96B	Heavy Duty Sliding Tray
WA-SW10-M6	Cabinet/ Rack Screw Kit
WA-SW20-M6	WA-Screws of Cabinet Cage

WO22AB

22U 4 Post Open Frame Rack



* devices not included

Specifications	
Color	Black
Industry Standard	ANSI/EIA RS-310D, DIN41491, PART1, IEC297-2, PART7, GB/T3047.2-92
Internal Dimensions	Outside Post-to-post [Depth]: Max:31.5" / Min:9.5"; Inside Post-to-post [Depth]: Max:23.5" / Min:2.0"; Hole-to-hole [Depth]: Max:27.35" / Min:5.5";
Surface Treatment	Degreasing, Phosphoric, and Powder Coat
Packaging Dimensions (W x H x D)	23.23 x 45.28 x 11.22 inch

CLANTEK Enclosed Cabinet

WO36AB

36U 4 Post Open Frame Rack



Specifications	
Color	Black
Industry Standard	ANSI/EIA RS-310D, DIN41491, PART1, IEC297-2, PART7, GB/T3047.2-92
Internal Dimensions	Outside Post-to-post [Depth]: Max:31.5" / Min:9.5"; Inside Post-to-post [Depth]: Max:23.5" / Min:2.0"; Hole-to-hole [Depth]: Max:27.35" / Min:5.5";
Surface Treatment	Degreasing, Phosphoric, and Powder Coat
Packaging Dimensions (W x H x D)	23.23 x 70.08 x 11.22 inch

WO45AB

45U 4 Post Open Frame Rack



Specifications	
Color	Black
Industry Standard	ANSI/EIA RS-310D, DIN41491, PART1, IEC297-2, PART7, GB/T3047.2-92
Internal Dimensions	Outside Post-to-post [Depth]: Max:31.5" / Min:9.5"; Inside Post-to-post [Depth]: Max:23.5" / Min:2.0"; Hole-to-hole [Depth]: Max:27.35" / Min:5.5";
Surface Treatment	Degreasing, Phosphoric, and Powder Coat
Packaging Dimensions (W x H x D)	23.23 x 90.12 x 11.22 inch